

ARYAVART BANK, HEAD OFFICE, LUCKNOW, UTTAR PRADESH.

<u>Inviting Tender for Furnishing Work at Aryavart Bank, NBCC Commercial</u>
<u>Complex, Gomti Nagar Extension, Lucknow</u>

Last Date & time for Submission of Bid: 07.10.2024 (02.00 PM)

AT

Head Office A-2/46, Vijay Khand, Gomti Nagar, Lucknow-226010

Architects

Point Architects Pvt. Ltd., Ground Floor, Royal Court, 4/45, Wazir Hasan Road, Lucknow – 226 001 Uttar Pradesh Telephone No. - 0522 - 4073807



INDEX

- 1. NOTICE INVITING TENDER
- 2. INSTRUCTIONS TO BIDDERS
- 3. FORMAT OF THE FORM FOR BIDDERS (TO BE SUBMITTED AS COVERING WITH THE BID)
- 4. CONDITIONS OF CONTRACT
- 5. IMPORTANT TENDER CONDITIONS
- 6. TECHNICAL SPECIFICATIONS
- 7. LIST OF APPROVED MATERIALS & MAKES OF FURNISHING ITEMS.
- 8. SCHEDULE OF TENDER DRAWINGS FOR FURNISHING WORKS
- 9. BILL OF QUANTITIES INCLUDING SPECIFICATIONS FOR FURNISHING WORKS (Financial Bid)
- 10. DRAWINGS 1 **NO**.



1.0 NOTICE INVITING TENDER

Tender Reference number (RFP)	110/100/1/10/1000
	HO/A&S/443/2024-25 Dated 12.09.2024
Tender Fee	Rs. 5,000/- * (Non Refundable) in the form of Demand Draft or Pay order Payable to Aryavart Bank , Lucknow or Payment through NEFT at following A/c-99990200000034 IFSC-BKID0ARYAGB, Gomti Nagar Branch, Aryavart Bank Lucknow
Date of commencement of issue of Tender document	12.09.2024
Last date for receiving queries	24.09.2024 up to 02:00 PM
Pre-bid meeting at bank's Head Office at A-2/46, Vijay Khand, Gomti Nagar, Lucknow-226010	25.09.2024 at 04:00 PM
Earnest Money Deposit	Rs. 2,00,000/- (Refundable) in the form of Demand Draft or Pay order Payable to Aryavart Bank, Lucknow or Payment through NEFT at following A/c-99990200000034 IFSC-BKIDOARYAGB, Gomti Nagar Branch, Aryavart Bank Lucknow
Last Date and Time for submission of bids	07.10.2024 up to 02.00 PM
Opening of Technical Bids	07.10.2024 at 03:30 PM at Bank's Head Office (subject to availability of Tender Committee members)
Place of Opening Technical Bid	Aryavart Bank
	Head Office: A-2/46, Vijay Khand, Gomti Nagar, Lucknow 226 010.
Address of Communication	As above
Contact Telephone Numbers	Phone :7388899765, 7017805214,9690347783
Email Id	ho.ans@aryavartbank-rrb.com
Website	www.aryavart-rrb.com
Architect	Point Architects Pvt. Ltd.,Ground Floor, Royal Court, 4 / 45, Wazir Hasan Road, Lucknow - 226 001.
Estimated Project Cost	Rs. 2,30,00000.00



Subject - Furnishing Works for Aryavart Bank at Head Office, Lucknow.

Item wise sealed tenders are invited in a two bid system for the above mentioned work for which tender document can be downloaded from the website of the bank at www.aryavart-rrb.com

Sealed bids in two envelop system (part A technical bid, part B financial bid) along with tender fee, earnest money deposit in the form of demand draft in favour of General Manager, Aryavart Bank, Lucknow, be submitted in a sealed cover & super scribed TENDER FOR FURNISHING WORKS FOR ARYAVART BANK AT HEAD OFFICE, LUCKNOW.

Tenders will be received on or before 07.10.2024 up to 02:00 PM and the technical bid shall be opened first to assess the technical soundness of the firm on 07.10.2024 at 03.30PM.

The financial bid will be opened for those firms only whose technical bid qualifies the technical evaluation criteria of the bank. Any tender received thereafter will not be accepted.

The General Manager, Aryavart Bank shall not be bound to accept the lowest bid & reserves the right to reject any or all the tenders without assigning any reason.

The tender shall be valid for a period of ninety days from the date of opening of tender.

(Seal & Signature of Aryavart Bank)

(Seal & Signature of contractor)

BASIC INFORMATION

	Name of the Applicant / Organization			
\vdash				
	Address of the Registered Office			
	(with phone numbers, e-mail ID & cell phone number)	e		
	Address of Office at Lucknow			
	(with phone numbers, fax numbers & e-mai	,		
	ID)	1		
;	Year of establishment			
<u></u>		^		
-	Type of the organization (whether sole			
	proprietorship, partnership, Private Ltd or Ltd.	. 1		
	Co. etc.) (Enclose certified copies of documents as evidence)	f		
4	Name & qualification of the proprietor /			
	partners / Directors of the organization / Firm			
	a)			
	b) *			
	c)			
	(Enclose certified copies of documents as	1		
	evidence)			
5	Details of registration – Whether Partnership			
	IIIIII, company, etc. Name of Registering			
	Authority, Date and Registration number			
	(Enclose certified copies of documents as			
6	evidence)	×		
Ü	Whether registered with Government / Semi-Government / Municipal authorities of any			
	other Public organization and if so, in which			
	class and since when? (Enclose certified copies			
	of documents as evidence)			
7	Details of registration with	Year of	Class	Validity
	(Enclose certified copies of documents as	Registration.	Class	Valid Up to
	evidence)			
			F	
7A	Number of years of owner			
11	Number of years of experience in the field and details of work in any other field			
8	Address of the office through which the			
	proposed work of the Bank will be handled			
	and the name & designation of Officer in			
_	Charge			
9	Yearly turnover of the organization during last 1	1. 2021-22-		
	3 years (year-wise) and furnish audited 2	2. 2022-23-		
	balance sheet and Profit & Loss a/c (audited) 3	3. 2023-24-		
\vdash	for the last 3 years. CA certificate required.			

		-
1	Name & Address of Bankers	
-	Name & Address of Bankers	1.
		2.
		3.
11	anciose copy of idlest income fay clearance	3
12	certificate	
12	PAN Number	
13	Details of registration for payment of service	
	tax .	
14	between description and value of works done	
15	Poteila (Proforma 2)	
15	Details of Key Personnel Permanently employed (Proforma 3)	
16	Other infrastructural information to be used /	
	_ referred for this project (Proforma 4)	
17	Furnish the names of 3 (three) responsible	
	persons along with their designation address	
	telephone no. etc. for whose organization, you	
	have completed the above mentioned jobs and who will be in a position to certify about the	
	performance of your organization	
18	Whether any Civil Suit / litigation arisen in	Attach a congrete chart is
	contracts executed / being executed during the	Attach a separate sheet, if required.
	last 10 years. If yes, please furnish the name of	
	the project, Bank, nature of work, contract	
	value, work order and brief details of litigation. Give name of court, place, status of pending	
	litigation.	
19	Information relating to whether any litigation	
	is pending before any Arhitrator for	
	adjudication of any litigation or else any	
	litigation was disposed off during the last ten	
	years by an arbitrator. If so, the details of such litigation are required to be submitted.	
	d to be submitted.	



Signature & seal of the Applicant

2.0 INSTRUCTION TO BIDDERS

- 2.1 SCOPE OF BID
- 2.2 ELIGIBLE BIDDERS
- 2.3 QUALIFICATION OF THE BIDDER
- 2.4 ONE BID PER BIDDER
- 2.5 COST OF BIDDING
- 2.6 SITE VISIT
- 2.7 CLARIFICATION OF BIDDING DOCUMENTS
- 2.8 AMENDMENT TO BIDDING DOCUMENT
- 2.9 ALL DOCUMENTS RELATING TO THE BID SHALL BE IN ENGLISH LANGUAGE ONLY
- 2.10 BID PRICES
- 2.11 BID VALIDITY
- 2.12 BID SECURITY (EARNEST MONEY)
- 2.13 FORMAT & SIGNING OF BID
- 2.14 SEALING & MARKING OF BIDS
- 2.15 LATE BIDS
- 2.17 MODIFICATION & WITHDRAWAL OF BID
- 2.18 BID OPENING
- 2.19 PROCESS TO BE CONFIDENTIAL
- 2.20 CLARIFICATION OF BIDS
- 2.21 EXAMINATION OF BIDS & DETERMINATION OF RESPONSIVENESS
- 2.22 CORRECTION OF ERRORS
- 2.23 EVALUATION & COMPARISON OF BIDS
- 2.24 AWARD CRITERIA
- 2.25 BANK'S RIGHT TO ACCEPT ANY BID & TO REJECT ANY OR ALL BIDS
- 2.26 NOTIFICATION OF AWARD & SIGNING OF AGREEMENT
- 2.27 DEFECTS LIABILITY PERIOD
- 2.28 COMPENSATION FOR DELAY
- 2.29 ADVANCE PAYMENT
- 2.30 SECURITY DEPOSIT



2.1 SCOPE OF BID

- 2.1.1 The General Manager, Aryavart Bank, Lucknow, Uttar Pradesh invites bids for Furnishing Works (as defined in these documents & referred to as "the works") detailed herewith.
- 2.1.2 The successful bidder will be expected to complete the work / s by the intended completion date & to the desired quality as specified in the contract data.

2.2 ELIGIBLE BIDDERS

- 2.2.1 The invitation to bid is open to all bidders within Union of India.
- 2.2.2 All bidders shall provide in section 3.0 forms of bid & qualification information, a statement that bidder is not associated, nor has been associated in the past, directly or indirectly, with the consultant or any other entity that has prepared the design, specifications & other documents for the project or being proposed by the Head Office Aryavart Bank, Lucknow or any of it's officers.

2.3 QUALIFICATION OF THE BIDDER

- 2.3.1 All bidders shall provide in the section 3.0 forms of bid & qualification information, a preliminary description of the proposed work method & schedule, including drawings & charts (as necessary).
- 2.3.2 All the bidders should submit the following documents with their bids -
 - (a) Proof of definition of the constitution or legal status, place of registration & principal place of business; written power of attorney of the signatory of the bid of commit the bidder.
 - (b) Total monetary value of construction work performed for each of the last five years.
 - (c) Experience in works of a similar nature & size for each of the last five years.
 - (d) Qualifications & experience of key site management & technical personnel proposed for the contract.
 - (e) Reports on the financial standing of the bidder, such as profit & loss statements & auditor's reports for the past five years.
 - (f) Evidence of adequacy of working capital for this contract.
 - (g) Information regarding any litigation, current or during the last five years, in which the bidder is involved, the parties concerned & disputed amount. (Including income tax, G.S.T. & service tax authorities).
 - (h) Proposals to subcontracting components of the works amounting to more than 10% of the contract price (if permitted & necessarily to be vetted by the architect).
 - (i) Income tax permanent account of the bidder.
 - (j) Income tax clearance certificate for the current financial year.
 - (k) G.S.T. Registration no.
 - (l) Any additional information as needed in the contract document.
- 2.3.3 Bids from joint ventures are not acceptable.
- 2.3.4 To qualify for award of the contract, each bidder in it's name should have following:
 - (a) **Requirement for Work Orders:** Experience of having successfully completed similar works during last **5 years** ending last day of month previous to the one in which applications are invited should be:

1. Minimum Work Order Value:

- Bidders must submit work order not more than 8 in number (during lasy 5 year) related to furnishing work, with a combined value of Rs. 200.00 Lakh or more.
- 2. Work Order Details:
 - Each of the submitted work orders must pertain specifically to furnishing work for PSB/PSU/Government entity.
- 3. Mixed Work Orders:
 - o If any work order includes additional types of work beyond furnishing work, the value attributed to furnishing work within that order should be proportionally calculated. For instance, if a work order includes both furnishing and other types of work, only the portion related to furnishing work will count towards the Rs. 200.00 Lakh requirement.

4. Documentation:

 Bidders should provide clear documentation for each work order to demonstrate that the work performed meets the specified requirements and that the furnishing work can be distinctly identified and quantified.

** Similar work means Furnishing Work for PSB/PSU/Government entities.

- (b) Annual average turnover of last three financial years (in all classes of Furnishing Work only) should be minimum **Rs. 900.0 Lakh & must be** supported by audited balance sheets along with CA Certificate of the same.
- (c) Any additional condition as imposed in the tender document.

2.4 ONE BID PER BIDDER

2.4.1 Each bidder shall submit only one bid. A bidder who submits or participates in more than one bid (other than as a sub-contractor or in the case of alternatives that have been permitted or requested) will cause all the proposals with the bidder's participation to be disqualified.

2.5 COST OF BIDDING

2.5.1 Tender fee is Rs. 5000/-, the application without tender fee shall be summarily rejected.

2.5.2 The bidder shall bear all costs associated with the preparation & submission of his bid, & the Bank will in no case be responsible & liable for those costs.

2.6 SITE VISIT

2.6.1 The bidder, at his own risk, cost & responsibility is encouraged to visit & examine the site of works & its surroundings & obtain all information that may be necessary for preparing the bid & entering into a contract for work/s.

2.7 CLARIFICATION OF BIDDING DOCUMENTS

2.7.1 A prospective bidder requiring any clarification regarding the bidding document may notify the Bank in writing with in predefined time or by cable (hereinafter "cable" included telex, facsimile, e-mail, hybrid mail, telegram) at the Bank's address indicated in the invitation bid. The Bank will respond to any request for clarification which he receives earlier than 7 days prior to the deadline for the submission of bids. Copies of the Bank's response will be forwarded to all purchasers of the bidding documents, including a description of the enquiry but without identifying its source.

2.8 AMENDMENT TO BIDDING DOCUMENT

2.8.1 Before the deadline for the submission of the bid, the Bank may modify the bidding documents by issuing addenda in Bank's website, www.aryavart-rrb.com.

2.8.2 Any addendum thus issued shall be part of the bidding documents & shall be communicated in writing through Bank website or by cable to all purchasers of the bidding documents. Prospective bidders shall acknowledge receipt of each addendum by cable to the Bank. For this purpose it is mandatory for all prospective bidders to furnish a mob no. at the time of purchase of the document.

2.8.3 To give prospective bidders reasonable time in which to take an addendum into account in preparing their bids, the Bank shall extend as he thinks if necessary the deadline for submission of the bids. The discretion to do so & the time to be extended would be the privilege of the Bank.

2.9 ALL DOCUMENTS RELATING TO THE BID SHALL BE IN ENGLISH LANGUAGE ONLY.

2.10 BID PRICES

2.10.1 The contract will be for the whole work based on the priced bill of quantities submitted by the bidder.

2.10.2 The bidder shall fill in rates & prices for all items of the works described in the bill of quantities. Items for which no rate or price is entered by the bidder will not be paid for by the Bank when executed & shall be deemed covered by the other rates & prices in the bill of quantities. Corrections, if any, shall be made by crossing out, initialing, dating & rewriting.

- 2.10.3 All duties, taxes & other levies payable by the contractor under the contract or for any other cause shall be included in the rates, prices & total bid price submitted by the bidder.
- 2.10.4 The rates & prices quoted by the bidder shall be fixed for the duration of the contract & shall not be subject to adjustment on any account.

2.11 **BID VALIDITY**

- 2.11.1 Bids shall remain valid for a period not less than one hundred eighty days after the deadline date for the bid submission. A bid valid for shorter period shall be rejected by the Bank as nonresponsive.
- In exceptional circumstances, prior to expiry of the original time limit, the Bank may request that 2.11.2 the bidders may extend the period of validity for a specified additional period. The request & the bidder's response shall be made in writing or by cable. A bidder may refuse the request without forfeiting his bid security. A bidder agreeing to the request will not be required or permitted to modify his bid except the validity period.

BID SECURITY (EARNEST MONEY) 2.12

- 2.12.1 As per section 1
- 2.12.2 No bank guarantees will be acceptable in lieu of the above.
- The bid security of the unsuccessful bidders shall be returned within 28 days of the end of the bid 2.12.3 validity period as specified in earlier section or earlier if the owner so desires. 2.12.4
- No interest whatsoever shall be payable on the said bid security.
- The bid security of the successful bidder shall be discharged after submission of Security Deposit 2.12.5

2.13 FORMAT & SIGNING OF BID

- The original copy of the bid shall be typed or written in indelible ink & shall be signed by a 2.12.1 person or persons duly authorized to sign on behalf of the bidder. All pages of the bid where entries or amendments have been made shall be initialed by the person / s signing the bid.
- The bid shall contain no alterations, except those to comply with instructions issued by the Bank, or as necessary to correct errors made by the bidder, in which case such corrections shall be initialed by the person/s signing the bid.

2.14 **SEALING & MARKING OF BIDS**

- The bidder shall seal the original bid in a non-transparent envelope duly marking it as original. 2.14.1 This envelope shall be kept inside another envelope which shall be sealed & signed across the joints by the person / s authorized by the bidder.
- 2.14.2 The inner & outer envelope shall be addressed to the Bank at the following address: General Manager.

Aryavart Bank, Head Office,

A-2/46, Vijay Khand, Gomti Nagar,

Lucknow.

Uttar Pradesh.

- The top of the envelope shall have clearly written in block letter the following -2.14.3 "BID FOR FURNISHING WORKS OF ARYAVART BANK, HEAD OFFICE, LUCKNOW."
- The lower left hand corner of the envelope, the name & address of the bidder along with the 2.14. telephone no. / s & fax. no./s should be inscribed.
- If the outer envelope is not sealed & marked as in 2.14.1, the Bank will assume no responsibility 2.14.5 for the misplacement or premature opening of the bid.
- 2.15 DEADLINE FOR SUBMISSION OF BIDS
- Bids must be received by the Bank at the address specified above no later than 02.00 PM on 2.15.1 07.10.2024.
 - In the event of the specified date for the submission of the bids is declared as a holiday by the Bank's organization, the bids will be received up to the appointed time on the next working day.
- The Bank may extend the deadline for submission of bids by issuing an amendment in which case 2.15.2 all rights & obligations of the Bank & the bidders previously subject to the original deadline will then be subject to the new deadline.

- 2.15.3 In case of the above, all those bidders whose names, addresses & mob nos. are in record with the Bank will be intimated by cable at least two days in advance of the proposed date of submission of the bid.
- 2.15.4 Those bidders who fail to register their name, addresses & mob no. with the Bank at the time of collection of the bid document shall have no right to 2.15.3 & cannot hold the Bank responsible for any damages whether direct or indirect.

2.16 LATE BIDS

2.16.1 Any bid received by the Bank after the deadline as prescribed earlier will be returned unopened to the bidder.

2.17 MODIFICATION & WITHDRAWAL OF BID

- 2.17.1 Bidders may modify or withdraw their bids by giving notice in writing before the deadline as prescribed in clause no.2.15
- 2.17.2 Each bidder's modification or withdrawal notice shall be prepared, sealed, marked & delivered in accordance with clause no.2.13 & 2.14 with the outer & inner envelopes additionally marked "MODIFICATION" or 'WITHDRAWL" as appropriate. No bids may be modified or withdrawn after the deadline for submission of bids.
- 2.17.3 Withdrawal or modification of the bid between the deadline for submission of bids & the expiration of the original validity period or extended as above will result in the forfeiture of the bid security.

2.18 BID OPENING

- 2.18.1 The Bank will open the bids, including the modifications in the presence on the bidders or their authorized representative / s who chose to attend at 3:30 PM on 07.10.2024 & place specified in the bid document. In the event of the specified date of the bid opening being declared a holiday by the Bank's organization, the bids will be opened at the appointed time & location on the next working day.
- 2.18.2 Envelopes marked withdrawal shall be opened & read out first.
- 2.18.3 The bidder's name, the bid price, the total amount of each bid & of any alternative bid (if alternatives have been requested & permitted), any discounts, bid modifications & withdrawals, the presence or absence of bid security & such other details as the Bank may consider appropriate, will be announced by the Bank at the opening. Any bid price, discount, or alternative bid price which is not read out & recorded at the bid opening will not be taken into account in bid evaluation.

2.19 PROCESS TO BE CONFIDENTIAL

2.19.1 Information regarding to the examination, clarification, evaluation & comparison of bids & recommendations for the award of a contract shall not be disclosed to bidders or any other persons not officially concerned with such process until the award to the successful bidder has been announced. Any effort by the bidder to influence the Bank's processing of bids or award decisions may result in the rejection of his bid.

2.20 CLARIFICATION OF BIDS

2.20.1 To assist in examination, evaluation & comparison of bids, the Bank may, at his discretion, ask any bidder for clarification of the bidder's bid, including breakdowns of unit rates. The request for clarifications & the response shall be in writing or by cable, but no change in the price of substance shall be sought, offered or permitted except as required to confirm the correction of arithmetic errors discovered by the Bank in the evaluation of the bids.

2.21 EXAMINATION OF BIDS & DETERMINATION OF RESPONSIVENESS

- 2.21.1 Prior to the detailed evaluation of bids, the Bank will determine whether each bid
 - (a) Meets the eligibility criteria defined in clause 2.2 $\&\,2.3$
 - (b) Has been properly signed
 - (c) Is accompanied with the required securities
 - (d) Is substantially responsive to the requirements of the bidding documents.

- 2.21.2 A substantially responsive bid is one which confirms to all terms, conditions & specifications of the building documents without material deviation or reservation. A material deviation or
 - (a) Which limits in any substantial way the scope, quality or performance of the works
 - (b) Which limits in any substantial way, inconsistent with the bidding document, the Bank's rights or the bidder's obligations under the contract
 - (c) Whose rectification would affect unfairly the competitive position of other bidders presenting substantially responsive bids.
- 2.21.3 If a bid is not substantially responsive, it will be rejected by the Bank, & may not subsequently be made responsive by correction or withdrawal of the non-confirming deviation or reservation.

2.22 **CORRECTION OF ERRORS**

- 2.22.1 Bids determined to be substantially responsive will be checked by the Bank for any arithmetic errors. Errors will be corrected by the Bank as follows -
 - (a) Where there is a discrepancy between the rates in figures & in words, the rate in words shall
 - (b) Where there is a discrepancy between the unit rate & the line item total resulting from multiplying the unit rate by the quantity, the unit rate as quoted will govern.
- 2.22.2 The amount stated in the bid will be adjusted by the Bank in accordance with the above procedure for the correction of errors & with the concurrence of the bidder, shall be considered as binding upon the bidder. If the bidder does not accept the correction amount, the bid will be rejected & the bid security may be forfeited.

2.23 **EVALUATION & COMPARISON OF BIDS**

- The Bank will evaluate & compare only bids determined to be substantially responsive in 2.23.1 accordance with clause no. 2.21 2.23.2
- In evaluating the bids, the Bank will determine for each bid the evaluated bid price by adjusting the bid price as follows:
 - (a) Making any correction for errors pursuant to clause no. 2.22
 - (b) Making appropriate adjustment for any other acceptable variations, deviations etc.
 - (c) Making appropriate adjustments to reflect discounts or other price modifications offered.
- The Bank reserves the right to accept or reject any variation, deviation or alternative offer. 2.23.3 Variations, deviations & alternative offers & other factors which are in excess of the requirements of the bidding documents or otherwise result in unsolicited benefits for the Bank shall not be taken into account in bid evaluation.

2.24 **AWARD CRITERIA**

- Subject to clause 2.25, the Bank will award the contract to the bidder whose bid has been 2.24.1 determined to be substantially responsive to the bidding documents & who has offered the lowest evaluated bid price. Provided that such bidder has been determined to be eligible in accordance with provisions of clause 2.2 & qualified in accordance with provisions of clause 2.3.It may be noted that having lowest bid is not the only criterion for award of the contract & does not guarantee the bidder of getting the contract.
 - Note: 1. In case of Tie between two or more bidder, bidder having highest turnover will get
 - 2. MSME bidders with valid certifications may receive preferences according to government guidelines

BANK'S RIGHT TO ACCEPT ANY BID & TO REJECT ANY OR ALL BIDS 2.25

Not withstanding clause 2.24, the Bank reserves the right to accept or reject any bid, & to cancel the bidding process & reject any or all bids at any time prior to award of contract, without thereby incurring any liability to the affected bidder or bidders or any obligation to inform the affected bidder or bidders of the grounds of the Bank's action.

NOTIFICATION OF AWARD & SIGNING OF AGREEMENT 2.26

- The bidder whose bid has been accepted will be notified of the award by the Bank prior to 2.26.1 expiration of the bid validity period by cable confirmed by registered letter. The letter (hereinafter & in the conditions of contract called the "letter of acceptance") will state the sum that the Bank will pay the contractor in consideration of the execution, completion & maintenance of the works by the contractor as prescribed by the contract (herein after called the
- The notification of award will constitute the formation of the contract subject to submission of 2.26.2 security deposit in the form of FDR in accordance with the provisions of clause 2.30.
- The agreement will incorporate all agreements between the Bank & the successful bidder. It will 2.26.3 be signed by the Bank & sent to the successful bidder within 28 days following the notification of award along with the letter of acceptance. Within 7 days of the receipt, the successful bidder will have to sign the agreement & deliver it to the Bank.
- If the successful bidder fails to do so, the Bank will assume that the successful bidder is unwilling to execute the contract & the bid security of the successful bidder will be forfeited
- In case of 2.26.4, the Bank reserves the right to award the contract to the next lowest bidder (If .2.26.5 CVC permits) provided he agrees to work on the same bid price as that of the successful bidder.
- The owner may, at his own discretion, in the event of 2.26.4 happening call for fresh bids. 2.26.6 2.26.7
- Upon the submission of the security deposit by the successful bidder, the Bank will promptly notify the other bidders that their bids have been unsuccessful.

2.27 **DEFECTS LIABILITY PERIOD**

Six months from the date of completion of work. 2.27.1

2.28 COMPENSATION FOR DELAY

2.28.1 Penalty for the delayed work / liquidated damages will be charged and payable @1% of the contract value per week up to a maximum of 5% of the contract value. In the event of the penalty charged exceeding 5% of the contract value, the Bank will be free to determine the contract after recovery of such charges from the security deposit and / or the retention amount. In case of any amount remaining outstanding, the same will be recoverable from any other works being carried out by you for the Bank or through appropriate legal action. In case of delays on the part of Bank, suitable extension of time will be granted but no other compensation will be paid for such delay.

2.29 ADVANCE PAYMENT

2.29.1 No advance payment whatsoever will be made to the successful bidder for mobilization or for any other reason/s.

2.30 **Security Deposit**

2.30.1 Successful firm/bidder is required to submit the Demand Draft/FDR of Rs. 10.00 Lakh in favor of Aryavart Bank as Security Deposit before receipt of letter of intent.



3.0 FORMAT OF THE FORM FOR BIDDER (TO BE SUBMITTED AS COVERING WITH THE BID)

To-

General Manager, Aryavart Bank, Head Office, A-2/46, Vijay Khand, Gomti Nagar, Lucknow. Uttar Pradesh.

Subject - Tender for Furnishing Works of Aryavart Bank at Head Office, Lucknow.

Sir,

- I / we submit tender for execution of work as mentioned above as per the tender documents within
 the time schedule of completion of work for jobs, as separately signed & accepted by me / us, at the
 schedule of rates quoted by me / us for the whole work in accordance with notice inviting tender,
 instructions to the bidder, conditions of contract, important tender conditions, technical
 specifications, list of approved materials, bill of quantities, drawings as per all other details given in
 the tender document.
- 2. It has been explained to me / us that the time stipulated for jobs & completion of works in all respects & in different stages mentioned in the time schedule of completion of jobs & signed & accepted by me / us is the essence of the contract. I / we agree that in the case of failure on my / us part to strictly observe the time of completion mentioned for job / s on any of them to the completion of job/s, I / we shall pay compensation to the owner as per the provisions & stipulations contained in the tender document & I / we agree to recovery being made as specified therein. In exceptional circumstances, extension of time will not be counted for the extension of completion dates stipulated for the job & for the final completion of work as stipulated in the said "time of schedule" of completion of jobs.
- 3. I / we agree to pay the security deposit & accept the terms & conditions laid down below in this respect:
- (a) Retention money: 5% of contract value will be deducted from each running / final bill of the contractor towards defects liability period.
- 4. Should this tender be accepted, I / we hereby agree to abide by & fulfill all terms & conditions to above & in default therefore, to forfeit & pay to the owner or its successors or it's authorized nominees such sums of money as are stipulated in conditions of contract.
- 5. If I / we fail to commence the work specified in the memorandum in para (2) above, or I / we fail to deposit the amount of security deposit specified in the memorandum in (3) above, I / we agree that the said owner or it's successor without prejudice to any other right or remedy be at liberty to forfeit the said security specified in (3) above. The said owner shall also be at liberty to cancel the notice of acceptance of tender in I / we fail to execute an agreement or to start work as stipulated in the tender documents.

DateDay	of2024

Name in block letters -

Address -

Yours faithfully,

Signature of tenderer / s with the seal of the firm

Name & designation of authorized person signing the tender on behalf of the tenderer / s -

4.0 CONDITIONS OF CONTRACT

- 4.1 DEFINITIONS
- 4.2 BANK'S RISK
- 4.3 CONTRACTOR'S RISK
- 4.4 INSURANCE
- 4.5 SAFETY
- 4.6 POSSESSION OF THE SITE
- 4.7 SAMPLES & SHOP DRAWINGS
- 4.8 TIME OF COMPLETION
- 4.9 WATER & ELECTRICITY
- 4.10 VIRTUAL COMPLETION
- 4.11 VARIATIONS
- 4.12 TYPE OF CONTRACT
- 4.13 SCHEDULE OF QUANTITIES & VARIATIONS
- 4.14 LICENSE & PERMITS
- **4.15 TAXES**
- 4.16 DELAYS
- 4.17 COMPENSATION FOR DELAY
- 4.18 LABOUR REGULATIONS
- 4.19 SECURITY
- 4.20 ESCALATION OF MATERIALS COST
- 4.21 EXTRAS & VARIATIONS
- 4.22 WITHHOLDING OF PAYMENTS
- 4.23 CORRECTION OF WORK BEFORE VIRTUAL COMPLETION OF WORK
- 4.24 DEFECTS
- 4.25 METHODS OF MEASUREMENT
- 4.26 DISMISSAL OF CONTRACTOR'S EMPLOYEES
- 4.27 TERMINATION OF THE CONTRACT BY THE OWNER
- 4.28 JURISDICTION
- 4.29 TESTS & CERTIFICATES
- 4.30 CLEANING THE SITE
- 4.31 OPERATIONAL CONSTRAIN



4.1 DEFINITIONS

- $4.1.1\,\mathrm{Bill}$ of quantities means the prices & complete bill of quantities forming part of the bid.
- 4.1.2 The contract is the contract between the Bank & the contractor to execute, complete & maintain the
- 4.1.3 The contractor is a person or corporate body whose bid to carry out work has been accepted by the
- 4.1.4 The contract data defines the documents & other information which comprise the contract.
- 4.1.5 The contractor's bid is the completed bidding document submitted by the contractor to the Bank.
- 4.1.6 The contract price is the price stated in the letter of acceptance & thereafter as adjusted in accordance with the provisions of the contract.
- 4.1.7 Days are calendar days & months are calendar months.
- 4.1.8The defects liability period is the period named in the contract data & calculated from the
- 4.1.9 The Bank is the party who will employ the contractor to carry out the works. In this case it will be -

Aryavart Bank, Head Office,

A-2/46, Vijay Khand, Gomti Nagar,

Lucknow.

Uttar Pradesh.

4.1.10 The Engineer / Architect is the person named in the contract data or any other competent person appointed & notified to the contractor to act as replacement to the engineer / architect) who is responsible for supervising the contractor, administering the contract, certifying payments due to the contractor, issuing & valuing variations to contract, awarding extensions of time (if permissible) & valuing the compensation events (if permitted). In this case the Engineer /

Point Architects Pvt. Ltd.,

Ground Floor, Royal Court,

4 / 45, Wazir Hasan Road,

Lucknow - 226 001.

- 4.1.11 Equipment is the contractor's machinery & vehicles brought temporarily to the site to construct
- 4.1.12 The initial contract price is the contract price listed in the Bank's letter of acceptance.
- The intended completion date is the date on which it is intended that the contractor shall complete the works. The intended completion date is specified in the contract data. The intended completion date may be revised only by the engineer in consultation with the owner by issuing an extension of time. 4.1.14
- Materials are all supplies, including consumables, used by the contractor for incorporation in the
- 4.1.15 The site is the area defined as such in the contract data which shall be:

NBCC Complex Gomti Nagar Extension, Aryavart Bank Head Office, Lucknow.

- Specification means the specification of the works included in the contract & any modification or addition made or approved by engineer / architect.
- The start date is given in the contract data, it is the date when the contractor shall commence execution of the works. It does not necessarily coincide with any of the site possession data.
- Temporary works are works designed, constructed, installed & removed by contractor which are needed for construction or installation of the works.
- 4.1.19 A variation is an instruction given by the engineer/architect which varies the work.

4.2 BANK'S RISK

- The Bank is responsible for the accepted risks which are -4.2.1
 - (a) In so far as they directly affect the execution of the work in the Bank's country, the risk of war, hostilities, acts of terrorism, riot, commotion of disorder(unless restricted to the contractor's
 - (b) A cause due solely to the design of the works, other than the contractor's design.



4.3 CONTRACTOR'S RISK

All risks of loss of or damage to physical property & of personal injury & death which arise during & in consequence of the performance of the contract other than the accepted risks are the responsibility of the contractor.

4.4 INSURANCE

Before commencing the execution of works, the contractor without limiting his obligations & responsibilities under this contract, shall ensure against his liability for any loss or injury which may occur to any person including any employee of the owner or a member of the general public, by or arising out of the execution of the work or in carrying out of the contract. Unless otherwise stipulated elsewhere in this contract, it shall be obligatory for the contractor to obtain the insurance cover under the following policy -

- (a) Contractor's all risks insurance policy to cover the following:
- (b) Policy to cover contractor's liability under workmen's compensation act 1923, minimum wages act 1948, contract labour (regulation & abolition act 1970 & other relevant acts listed elsewhere). This shall be for the period of compensation period.

The contractor shall insure against all such liabilities & shall continue such insurance during the whole of the time when any person employed by him is on the works. Premium for all insurance policies shall be paid by the contractor & shall not be reimbursable.

4.5 SAFETY

The contractor shall be responsible for the safety of all activities/personnel on the site.

4.5 DISCOVERIES

Anything of historical or other interest of significant value unexpectedly discovered on the site is the property of the Bank. The contractor is to notify the engineer of such discoveries & carry out the engineer's instructions for dealing with them.

4.6 POSSESSION OF THE SITE

The Bank shall give possession of all parts of the site to the contractor. If possessions of a part are not given by the date stated in the contract data, the Bank is deemed to have delayed the start of the relevant activities.

4.7 SAMPLES & SHOP DRAWINGS

After the award of the contract, the contractor shall furnish for the approval of the architect, samples & shop drawings (where appropriate) for all materials, finishes & work listed elsewhere in these conditions.

4.8 TIME OF COMPLETION

The work shall be completed in all respects within **75 days** (including holidays & Sundays) from the date of award of work inclusive of mobilization period.

4.9 WATER & ELECTRICITY

These shall be arranged by the owner at one or more convenient point/s. Necessary extensions of these supplies will have to be got executed by the contractor at his own cost.

4.10 VIRTUAL COMPLETION

Virtual completion certificate shall mean the certificate / s to be issued by the architect when the "works" according to the architect have been completed in every respect in conformity with the contract documents & are ready & fit for occupation / commissioning.

4.11 VARIATIONS

The owner reserves the right to increase, decrease or delete the scope of work or any or all items, subject to limitation laid down. The contractor shall have no claim for loss of anticipated profits or for any other reason whatsoever on account of these variations.



4.12 TYPE OF CONTRACT

The contract shall be an item rate contract. The contractor shall be paid at the contract rates, for the actual quantity of the work carried out by him as measured, in accordance with the contract

SCHEDULE OF QUANTITIES & VARIATIONS 4.13

The quantities given in the schedule of quantities are provisional & are meant to indicate the intent of work & provide a uniform basis for tendering. The contractor shall be paid for the actual quantity of work executed by him in accordance with the right to increase or decrease any of the quantities or totally omit any items of work & the contractor shall not claim any extra or damages on these grounds subject to the condition that the overall contract amount is not varied by more than +- 50%.overall contract amount, for the purpose of variation shall not take into account the additions to the total amount because of escalation of price materials, labour, etc. Any error in description or in quantity or omission of item in the schedule of quantities shall not vitiate this contract but shall be deemed to be a variation required by the architect.

4.14 **LICENSE & PERMITS**

License & permits for all materials under the govt. control shall be obtained by the contractor directly. The contractor shall include in his tender all transport charges & other expenses that may be incurred in this connection.

4.15 **TAXES**

The rates quoted by the contractor for each item shall be inclusive of all taxes, such as sales tax both central & state), trade tax, income tax, turnover tax, works contract tax, excise duty, octroi etc. complete on all materials & equipment forming part of the work.

4.16 **DELAYS**

Should the contractor be delayed or impeded in the execution of works by reason of:

- (a) Force mejure.
- (b) By the works or delays of other contractors or tradesman, engaged or nominated by the owner & not referred to in the contract document.
- (c) The non-delivery or delay in the delivery to the contractor of any materials & equipment which under the contract the owner or the architect; or
- (d) Any cause, whatever arising out of the acts of defaults of the owner or the architect; or
- (e) Any accident happening to the works during the progress not arising from negligence, default of the contractor or his workmen or subcontractor; or
- (f) Extras or variations being ordered by the architect; or
- (g) Any other cause which is in the opinion of the architect has caused delay, the contractor may from time to time within 14 working days of the happenings of any of the aforesaid, writing to the architect for an extension of time on account thereof, setting forth the cause of such

The architect / owner shall, if he thinks the cause sufficient but not otherwise, by writing within 14 working days extend the time of completion of the works for such periods as he shall think adequate.

Unless the contractor shall ask for any extension of time within the period & the manner aforesaid,* unless & until the architect / owner shall extend the time aforesaid, the contractor shall not by reason of any delay arising from cause aforesaid, be relieved in any way or to any extent from his obligation to proceed with, execute & complete the works within the time specified in the contract for the completion of the work.

4.17 **COMPENSATION FOR DELAY**

The contractor shall not be entitled to any compensation for any loss suffered by him on account of delays in commencing or executing the work whatever the cause of delays arising out of modification of the work entrusted to him or in any sub contracts connected therewith or delays in contracts for other trades of the project or in commencement of completion of such works.



4.18 LABOUR REGULATIONS

The contractor shall be wholly & solely responsible for full compliance with the provisions under all labour laws of the Union of India &/or regulations such as payment of wages act 1936, minimum wages act 1948 & it's subsequent amendment/s.

4.19 SECURITY

It will be responsibility of the contractor only.

4.20 ESCALATION OF MATERIAL'S COST

It is a fixed rate contract, no escalation either on materials or labour whatsoever shall be paid under any circumstances.

4.21 EXTRAS & VARIATIONS

If, at any time while the works are in progress, the architect deems it necessary to order materials or work of a different description from what was originally specified, the architect has full authority to direct any such variations or additions. The contractor must execute any work involved in these variations or additions if it falls within the class of work covered by the contract documents. The time for completion may be extended as needed. Payment for these additions or variations will be made or deducted from the contractor's account according to the rates specified in the schedule of quantities.

The rates for such additional altered or substituted work under this clause shall be worked out in accordance with the following provisions in their respective order -

(a) If the rates for the additional, altered or substituted work specified in the contract for the work, the contractor is bound to carry out the additional, altered or substituted work at the same rate as specified in the contract for work.

(b) If the rates for the additional, altered or substituted work are not specifically provided in the contract for the work, then such rates will be derived from the rates for a similar class of work as specified in the contract for work.

(c) If the altered, additional or substituted work cannot be derived from similar class of work as laid down in (b) above, then the rates for such items of work shall be completed on the basis of the analysis of rates as provided in all schedule of rates 1977-III standard analysis of rates (volume I & 2) published by national building organization, New Delhi.

But if the contractor & architect cannot agree as to the rate to be paid, the architect may order & direct the same to be done by such person/s as he may think fit & such person/s shall be permitted by the contractor to enter upon the works for the purpose of carrying out such work/s as is required.

4.22 WITHHOLDING OF PAYMENTS

The architect may withhold or on account of subsequently discovered evidence, nullify the whole or a part of any certificate to such extent as may be necessary to protect, the owner from loss on account of -

- (a) Defective work not remedied.
- (b) Failure of the contractor to make payments to sub-contractors (if permitted) for materials or labour or equipment's.
- (c) A reasonable doubt that the contract can be completed for the balance unpaid amount. Damage of works of another contractor or sub-contractor.

4.23 CORRECTION OF WORK BEFORE VIRTUAL COMPLETION OF WORK

The architect shall conduct a final inspection just prior to the virtual completion of the work & prepare a list of materials, equipment & items of work which fail to confirm to the contract specifications. The contractor shall promptly replace & re execute such items in accordance with the contract & shall bear all expenses of making good all work & the cost work of other contractors destroyed or damages by such replacement or removal. If the contractor fails to remove & replace above, rejected materials, equipment & or workmanship within a reasonable time, fixed by written notice, the owner may employ any other persons to amend & make good such defects at the expense to the contractor.



All expenses incurred by the owner in consequent on the defects shall be recoverable from any amount due or that may become due to the contractor.

4.24 VIRTUAL COMPLETION

The work shall be considered to be virtually complete only upon fulfillment of the procedure laid down in clause above & when the architect has certified in writing that the work has been virtually completed. The defects liability period shall commence from the date of the certificate. Should the owner decide to occupy any portion/s of the building or use any part of any equipment, before the contract is completed, same shall not constitute as acceptance of any part of the work unless so stated in writing by the architect.

4.25 DEFECTS

- 4.25.1 The contractor shall make good, at his own cost & to the satisfaction of the architect from work of materials not being in confirmation of the drawings or specifications or schedule of quantities or the specifications of the architect, which may appear within six months after completion of work.
- 4.25.2 Any defects noticed & brought to the attention of the contractor shall be promptly attended to by the contractor expeditiously.
- 4.25.3 After the contract is signed, the contractor will be furnished with two copies of the drawings & two copies each of conditions & contract, specifications & schedule of quantities without cost to him for his own use until the completion of the contract. Additional copies of the drawings & other documents will be supplied on payment to the architect at actual cost.

 In general, the drawings shall indicate dimensions, position & type of construction; the specification shall indicate the quantity & rate for each item of work. However the above documents being complementary, what is called for by any one shall be binding as if called for by all. In case of any discrepancies in or among the documents, the most stringent of all shall apply. No deviations from the drawings, specifications & schedule of quantities shall be made. The architect's interpretation of these documents shall be final & without appeal.

4.26 METHODS OF MEASUREMENT

For measuring of work, the standard method of measurement in accordance with the standards laid down by the BIS shall be adopted unless otherwise specified. In the event of any dispute with regard at the mode of measurement of the work executed, the decision of the architect shall be final & binding.

4.27 DISMISSAL OF CONTRACTOR'S EMPLOYEES

The contractor shall on request of the architect immediately dismiss from the works of any person/s employed thereon by him who may, in the opinion of the architect be incompetent misconduct's himself & such person shall not be re-employed on the works without the permission of the architect.

4.28 TERMINATION OF THE CONTRACT BY THE OWNER

If the contractor should persistently or repeatedly refuse to carry on the work diligently or shall fail except in case for which extension of time is provided, to supply enough properly skilled manpower or proper materials or equipment for the progress of work, or if he should fail to make prompt payments to sub-contractors (if permitted) or for materials or equipment / s or labour or persistently disregard laws, ordinances or instructions of the architect or otherwise be guilty of a violation of any provision of the contract, or has abandoned the contract, or has failed to commence the works, or has suspended the works, then the owner upon the certificate of the architect that sufficient cause exists to justify such action say without prejudice to any other right or remedy & after giving the contractor seven days' notice in writing, terminate the employment of the contractor & take possession of the premises of all materials, equipment/s, T&P thereon & use these as owners property for the completion of the work. In such case, the contractor shall not be entitled to receive any further payment until the work is finished.

4.29 IURISDICTION

All matters arising out of or in way connected with this agreement shall be deemed to have arisen at Lucknow (Uttar Pradesh) & shall have jurisdiction to determine the same.



4.30 TESTS & CERTIFICATES

The contractor shall be & remain liable at his own cost to conduct all tests at all relevant times during supply, erection & installation of any works, structures, materials & components as shall be required in terms of the contract document. On testing if the architect is not satisfied by the quality of workmanship of any structure, material or component, the contractor shall re perform as per the specifications?

4.31 CLEANING THE SITE

The contractor shall be responsible for removing malba from the site to place permitted by the municipal authorities every 48 hours & cleaning the site regularly. Cost of removal of malba, transportation, loading, unloading etc. (up to any lead) shall be included in the cost of the relevant item of construction.

4.32 OPERATIONAL CONSTRAIN

This is a relocation branch & the space is freely available during period of execution.

5.0 IMPORTANT TENDER CONDITIONS (over riding any other condition laid down earlier)

1	- TOO COOLON OF DICC	Immediate
2	Time of Completion	75 days from the date of handing over the site
3	Payment Schedule	No advance payment will be made. Only one interim payment can be made on running bills before the final bill. The interim payment may be processed after the completion of 60% of the work.
4	Retention Money	5% (five percent only) of the value of the interim bills.
5	Period for Submitting Final Bills	Within 30 days of virtual completion of work.
		(a) 50% of the retention amount within 30 days of final completion. (b) Balance after 6 months from the date of completion certificate and after discharge of
6	Release of Retention Money	defects liability.
7	Defects Liability	6 months from the date of completion.
8	Estimated Cost of Work	As per Section 1.
9	Income Tax & Other Taxes	Will be deducted as per the prevailing income tax, works contract tax, etc. laws.
10	Rates	Rates are inclusive of all taxes such as sales tax (state & central), trade tax, works contract tax, etc., except G.S.T. & state development tax, if asked for in the quotation. The contractor is expected to fill up the rate/amount of taxes in their bid, specifically in the given location. It should not be stated ambiguously as "taxes extra" at the end of the total tendered amount. The bank shall not be liable to pay any tax that is not specifically quoted or is ambiguous.



6.0 TECHNICAL SPECIFICATIONS

6.1 MATERIALS *

6.1.1 **Ouality**

All materials used in the works shall be of their respective kinds as specified herein, obtained from sources & suppliers as approved by the architects & shall comply strictly with the tests prescribed hereafter, or where tests are not laid down in the specifications, with the requirements of the latest issue of the relevant Indian standard.

6.1.2 Sampling & testing

All materials used in the works shall be subject to inspection & test in addition to test certificate of all materials proposed to be incorporated in permanent works shall be submitted to the architect for approval before they are brought to the site.

6.1.3 Rejection

Any materials that have been not found to confirm to the specifications will be rejected forthwith & shall be removed from the site by the contractor at his own cost. The architect shall have power to cause the contractors to purchase & use such material / s from any particular source / s as may in his opinion be necessary for the proper execution of the work.

6.2 WORKMANSHIP

All works shall be true to level, plumb & square & the corners, edges, etc. in all cases shall be unbroken & net.

Distempering, POP / Painting / Polishing shall be provided in accordance with CPWD specifications 1977 & relevant standards as applicable to this work. Painting with plastic emulsion paint (if required) shall be as per CPWD specifications 1977 & IS 5411-1969. Paint shall be of approved manufacturer & brand.

All timber shall be treated with preservatives before delivery to site. While remaining in proper wrapping, timber shall be protected from extremes of temperature & direct sunlight. Timber shall be soft wood or hardwood as suitable for the purpose for which it is intended. It shall be seasoned, free of defects which would affect strength or usability & shall be flat, non-splitting & dressed on all sides. All glue, laminate, ply, board shall be as per the relevant IS codes. Where ever teak is specified it shall be 1st. Class C.P. Teak. All aluminum work pre-laminated particle board work & glass work will be as per the relevant IS codes & their latest amendments.

6.3 **FINISH**

Finishes shall be fully in accordance with the drawings & schedules and / or as per the directions of the architect.

SAMPLES

A sample of every item to be incorporated shall be submitted for approval of the architect before placing the order. Approved samples shall be used as standards of finish & workmanship.



APPROVED MAKES FOR FURNISHING WORKS.

FURNISHING WORKS -

S.No.	Material	
1	Commercial Ply wood (6.0mm, 8.0mm, and 12.0mm)	Brand
2	Commercial Board (19mm and 25mm)	Amul/Archid/Euro/Kitply (Ozark)
3	B.W.P./Marine Ply wood (6.0mm, 8.0mm, and 12.0mm)	Amul/Archid/Euro/Kitply (Ozark)
4	B.W.P./Marine Board (19mm and 25mm)	Amul/Archid/Euro/Kitply (Ozark)
5	Wood (under framing)	Amul/Archid/Euro/Kitply (Ozark)
6	Wood (beading, moulding, cornices, lipping, footrest,	Kail/Partal
7	Hailing	Teak Wood
-	Screws	GKW
8	Adhesive	Fevicol - SH
9	Anti-Termite	Trishul/Pentaphene (STP)
10	Laminate (1.5mm and 1.0mm)	oncaphene (STT)
11	Down Market Co.	Amulya/Formica/Archid/Sunmica/Panaash
	Decorative/Veneered Ply Wood	Century/Sun
12	Tack/Soft Board	Cellotex
13	Pre-laminated Particle Board	Easy Lam/Nepal Board/Novapan
14	Aluminium Sections & Grills	Indal/Hindalco
15	Aluminium Accessories	Classic (ISI)
16	Floor Springs	Everite
17	Hydraulic Door Closer	Godrej
18	Mortice & CAM Locks	Godrej
19	Night Latch Locks	Godrej
20	Gypsum Plaster Board	Gypsum India Ltd
21	Mineral Fibre Board	Armstrong/Insula
22	Metallic Ceiling	Luxolon/Trac
23	Flooring & Skirting - Laminated	Vista Floor Fashion/Formica
24	Flooring - P.V.C.	Armstrong/LG
25	Flooring - Vitrified	Murudeshwar Ceramics
26	Tile Adla :	Ltd./Restik/Asian
27	Tile Adhesive	Uni tile
	Handles, Guides, Sliding Units, Hinges, and Magnetic Catchers	Hettich/Earl Bihari
28	Textured Wall Finish	Spectrum/Acro
29	Acrylic Emulsion & Primer	Asian/Berger/Nerolac
30	Synthetic Enamel & Primer	Asian/Berger/Nerolac
31	Oil Bound Distemper & Primer	Asian/Berger
32	Upholstery	Vista Home Fashions/Vimal
	Blazer Cloth	Raymonds
34	Foam	Sleep Well
35	Rubber Solution	Dunlop S-758/Fevicol - SR
		Damob 2-120/L6AICOI - 2K
	Castors	Jaiswal/Roll on/Champion



38	Gas Lift	
39	Chair Base	Suspa
40	Glass	Commander
41	Drapery Rod	Modi Guard
42		Vista Levolar
43	Vertical Blinds	Vista Levolar
44	Curtain	Vista Home Fashions/Vimal
- 2004	Sun Control Films	Garware
45	Moulded Furniture	Cello/Nilkamal
46	Fiberglass Sheet	Paxiglas
17	Carpet - Woven (Woolen/Synthetic)	
18	Carpet - Non Woven	Transasia
		Unitex




SCHEDULE OF TENDER DRAWINGS FOR FURNISHING WORKS

S.NO.	DRAWING NO.	TITLE OF DRAWING
1.	01	FURNISHING LAYOUT PLAN


• Any clarification (in writing) whatsoever shall be sought from the Architect, minimum two (2) days before the tender submission date.

(P. V. Sahai) Chief Manager













ARYAVART BANK, HEAD OFFICE, LUCKNOW, UTTAR PRADESH.

Financial Bid (Bill of Quantity)

Architects

Point Architects Pvt. Ltd., Ground Floor, Royal Court, 4/45, Wazir Hasan Road, Lucknow – 226 001 Uttar Pradesh Telephone No. - 0522 - 4073807



S.NO.	DESCRIPTION	QTY	. UN	T	DATE	
1	Gypsum Board False Ceiling				RATE	AMOUNT
2 AP tri H mail FF XI so had Ma 60 Cro An by Ma Wh sha	Providing & fixing as per design with suspended false ceiling consisting of 12mm. thick Gyp. board suspended on G.I. framework to consists G.I. perimeter channels -0.55 mm thick x 20mm x 30mm. alor perimeter of false ceiling; screw fixed to wall/partition with nylon sleeved & screws @ 600mm. dc. Suspending GI. Interme diate channels of siz 0.9mm thick x45mmx15mm. from the soffit at max. distance 1220mm dc with ceiling angle 0.55 mm. thick x 2n5mm.x10mm. Fixed to soff using proprietary supplied GI. Cleats & steel expansion fasteners. Ceiling section 0.55mm thick x web size 51.5mm & flanges 26mm. Eac 24.10.5 mm. lips fixed perpendicular to intermediate channel at 457mm. Cr. Gyp board is screw fixed to ceiling section with 25mm. drywascrews at 230mm. c/c. boards to be finished with proprietary supplied inish etc.complete or as directed by the Architec/Bank. Gyp ceiling where necessary as normal specification Rate should include all types of cut-outs, grooves ,moulding & plain troughs for tube lights / Down ighter as directed by the designer. Note: Where RCC Slab is old and oncrete is weal, the GI suspended channel shall be fixed with epoxy intermediate channel. Inmstrong False Ceiling Troviding and fixing of Armstrong make Mineral fibre Ceiling Boards in use horizontal level suspended on inter locking Grid system made of of Dip Galvanized steel sections powder coated XL -15 mm as per anufacturers specification including making opening for electrical and reconditioning fitting complete as directed. The tiles and grid system RAMEWORK 15 mm Main Runner of 3000mm spaced at 1200mm centre fixed to fift by approved hangers at 1200mm distance. First and last neger should not be at a distance more than 450mm from the jacent wall.XL-15 mm 1200mm cross Tee to be interlocked between a finance at 600mm centre to form 1200x600mm module. Ommx600mm module to be formed by fixing XL-15mm 600mm comms Tee between centre of 1200mm Cross Tees 19X19 mm Wall gle to be secured to wall at 450mm centers Suspension to be done using 2mm p	of ng es e.e. n. fit s. h n.	Sq.F.t.	t.		Allicont
Mai	before fixing Gypsum board fixing.Rate shall be inclusive of epoxy emical and fixing of suspenders with chemical in Entrance Door with Partition (Toughened Glass)	495	C = 54			
toug nec polis Doo thick fittin deco expo	widing & fixing main door & partition made up of 12 mm thick Clear phened glass shall be fixed in Ozone / Enox make patch fitting with essary hardwear. With application of sealant from all sides. Edge sh for all exposed sides of glass. Complete as per design r size 7'0" x 3'0" - Providing & fixing main door made up of 12 mm c Clear toughen glass shall be fixed in Ozon / Enox make patch g with necessary hardware like floor spring, 12" S.S. finished prative handle pair, & locking arrangment. Edge polish for all psed sides of glass. Complete as per design.		Sq.Ft.			
Prov mm* horiz heigl	iding and fixing low height partition up to 4-6" height made out of 50 50mm 18mm Gauge aluminium frames at 2' C/C vertically & contally with 12mm thick commercial plywood on both sides upto 3' at and above portion with 10mm float glass Finished with 1.0 thick nate of approved shade and design.	3440	Sq.Ft.		5	



	5	Full Ht. Glazed Partition With Door					
		Providing & fixing 3" thick partly glazed partition with 10mm thick is		9210	Sq.Ft.		
		India glass for flade up of 18 dating soven mm Alimeir	27				·
		Individual at 000 IIIII C/C DOIN Ways (or as directed by the Architect)	40			1	
×		I'm commodal plywood & I mm laminate from both sides Destin			Ì		
		oriodia be initiating with specified finish as per design The retained	and the second				
- 1		providing 55 mill thick high door tinighed with 4 and 1	- 4				
		Sprioted make/shade on both sides with possess it.					1
		polished. Rate includes all necessary hardware (i.e ball bearing hing of approved make, door closure. Clindrical Late 1991)	ges				
		of approved make, door closure, Clindrical Lock with key, Door stopp etc) Exposed edges of the partition should have 75x12 mm matchi	per				
	- 1	with groove iii between All provisions to be made for	- 11				
		The state of the s	. 1				
		deligitional access with necessary additional access					
	- 1	balloung as required. The rate inclines all necessary hand	, oi				
	- 1	cleaning of partition to the satisfaction of the Architect etc. complete.	_			1	
		Solid Partition With Door					
	F	Providing & fixing 3" thick solid partition for made up of 18 gauges 50x50 mm Aluminium specified from the control of the cont	1	700	Sq.Ft.		
	- 1	the state of the s					
	١-	all color by the Alchitect). 12 mm commedial phases of					1
1	1	animate from both sides. Parifion should be finished with a se	141				1
1	1"	mier de per design. The fate includes providing 35 mm thick finale at	2000				
	1.	The recessary lipping patti polished Rate includes all					
	1	aldware (i.e ball bearing ninges of approved make deep					
	1-	midital book will key. Door stopper etc) Exposed adapt of the					
	11-	and official flave / DX /Z fifth matching wood Datti with and	- I				
	~	ottoon. All provisions to be made for all electrical naturality	201				
	w	elephone etc. boxes onto partition framework at required heights/level- rith necessary additional supports &/or scaffolding as required. The rate	s				
	in	cludes all necessary hardware & cleaning of partition to the	е				
7	·	/all Panelling	е				
	Pi	roviding and fixing panelling on wall / column made out of 50 mm	47	10	Sq.F.t.		
	50	Omm 18mm Gauge aluminium frames at 2' C/C vertically 8	X				
	1110	onzontally. This framing would be covered by 6mm thick Div and average	4				
1	1	insted with fillin thick laminate of approved shade and design at	il .				
1	100	inpicte.	"		1		
8	C	ote : Area behind storeage cabinet not considered for payment.					
-		idiffidit fable (0 -0	1		No		
	10	oviding & fixing table made up of 18 thick Comm. Plywood frame with	1				_
	thi	mm. thick Clear glass on top. The table should be finished with 1.0 ck Laminate on exposed plywood frame, inside edge of holes, polish			- 1		
	fro	m inside. The table shall be provided with single drawer, ply key					1
	100	and drawer, ply C.P.U. trolley with ply footrest wire manager & other	.1	- 1			
	liec	direct flatdware. The glass shall have plain diamond adds polich and	1				
	Į dii	The glass should cover the length		,			
	of t	the table & width of side unit as shown in the drawing.					*
9							
	Pro	Is Table (6'-0" x 2'-6" x 2'-6")	5		Nos.		
	10n	oviding & fixing table made up of 18 thick Comm. Plywood frame with nm. thick Clear glass on top. The table should be finished with 1.0					
	thic	sk Laminate on exposed plywood frame, inside edge of holes, polish					1
	lii Oii	if inside. The table shall be provided with single drawer bly key board					1
	Jula	Wel, ply C.F.U. Ifoliev with ply tootrest wire manager of the l					
	1,04	uned hardware. The glass shall have plain diamond adap notice and					
	Jan I	our sides a rible for wire manager. The glass should cover the longth					- 1
	of th	ne table & width of side unit as shown in the drawing.			- 1		
10	HOI	Os Table (5'0" x 2'6" x 2'6")					1
	Prov	viding & fixing table made up of 18 thick Comm. Plywood frame with	16	1	Nos.		
	1 10111	in. thick clear glass on top. The table should be finished with 1 of					
	Lillor	Laminate on exposed plywood frame, inside edge of holes, policial					
	Inom	inside. The table shall be provided with single drawer bly key board					
	ulavi	ver, ply C.P.O. trolley with ply tootrest, wire manager & other					
	Irequ	lifed flatdware. The glass shall have plain diamond edge police and					1
	Jan 10	our sides & note for wire manager. The glass should cover the length					1
	"	e table & width of side unit as shown in the drawing.					-
	/						
半年	//						

Providing & floring table made up of 18 thick Comm. Plywood frame. In table should be finished with 1.0 thick. Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P. Livolley with Ply footest, wire manager, & other required hardware. The glass shall manager The glass specified on all for single and provided the polish on all four sides & hole for wire manager. The glass shall manager The glass specified of the side of	Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with snigle drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. The glass shall be provided with snigle drawer ply key board drawer. Ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. The glass shall have plain diamond edge polish on all four sides & hole for vivie unit as shown in the drawind. 12 Doctors Table (4.0° x 2.0° x 2.0° x 2.6°) Same as items No.8 without key board drawer 13 Patients Examinatin Table (6.0° x 2.0° x 2.6°) Same as items No.8 without key board drawer 14 Guard's Table (2.9° x 2.0° x 2.6°) Same as items No.8 without key board drawer 15 Board Room Meating Table (1.6° x 3.0° x 2.6° x) Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood the bable should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table should be finished with 1.0 thick Laminate on exposed plywood frame, pixed for the providing & fixing table grade up of 18 thick Comm. Plywood framework. 14 Providing & fixing table grade up of 18 think Comm. Plywood framework. 25 Goron Toy For Tables. 26 Goron Toy For Tables. 27 Ho						
isable should be finished with 1.0 thick Laminate on exposed phywood farme, inside degd of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply CP. U. trolley with ply footnet, with emanager. 3 cherr required hardware. The glass shall be provided with single drawer, ply key board drawer, ply CP. U. trolley with ply footnets, with emanager. The plass shall be shall be provided with single drawer. So there required hardware the length of the table 8 width of side unit as shown in the drawing. 12 Doctors Table (4-0" x 2-0" x 2-0" x 2-0") 13 Patients Examinatin Table (6-9" x 2-0" x 2-0") 14 Guards Table (2-9" x 2-0" x 2-0") 15 Same as items No.8 without key board drawer 16 Doard Room Meating Table (15-0" x 2-0" x 2-0") 17 Providing 8 floring table made up of 18 link Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood table 4 with of side unit as plotted in the common should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table 8 width of side unit as shown in the drawing. 17 Work Table Running Counter Work Top (4-9" x 2-0" x 2-0") 18 Conference Table (102-0" x 2-0" x 2-0") 19 Providing 8 hong table made up of 18 link Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from	iable should be finished with 1.0 thick Laminate on exposed plywood fame. Inside degic polices, polish from Inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest. with emanager. 2. other required hardware. The gliass shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest. with emanager. The gliad of the shall be provided with a shown in the drawer with the shall be gliad of the	11	The state of the s	149	Nos.		
in Tame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply CPU troilley with ply footrest, wire manager, 8 other required hardware. The glass shall have plain climanid edge polish on all four sides 8 hole for wire manager. The glass should cover the length of the table 8 width of side manager. The glass should cover the length of the table 8 width of side manager. The glass should cover the length of the table 8 width of side manager. The glass should have been decided to the same as items No. 8 without key board drawer. 1 Patients Examinatin Table (4-9" x 2-4" x 2-4") 3 Patients Examinatin Table (4-9" x 2-4" x 2-4") 4 Guards Table (2-9" x 2-4" x 2-4") 5 Board Room Meating Table (1-9" x 3-4" x 2-4") Froviding 8 fising table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table 8 width of side unit as shown in the drawing. 10 Conference Table (102-0" x 2-0" x 2-4") 11 Providing 8 fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table 8 width of side unit as shown in the drawing. 11 Work Table Running Counter / Work Taple (4-8" x 2-4" x 2-5") 12 Work Table Running Counter / Work Taple (4-8" x 2-4" x 2-5") 13 Correct to glass the shown in the draware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel panted inside. 13 Correct to yow kind chairman, board room & conference room table 14 Work Table Running Counter / Work Taple (4-8" x 2-4" x 2-5") 15 Providing 8 fixing table made up of 18 mm. thick plywood framework should be finished with 1.0 thick Laminate on front and enamel panted inside. 16 Correct to yow kind chairman, board room & conference room table 17 Work Table Taples Correct to your pant to non laminat	rame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C-PL trolley with ply footrest, wire manager. 8 other required hardware. The glass shall nave plain diamond edge polish on all four sides 8, hole for virie manager. The glass should cover the length of the table 8 width of side manager. The glass should cover the length of the table 8 width of side manager. The glass should cover the length of the table 8 width of side manager. The glass should cover the length of the table 8 width of side with a series of the ser		table should be finished with a finished with	;			
provided with single drawer, ply key board drawer, ply CP-U, trolley with ply footrest, wire manager, 5, other required hardware. The glass shall have plain dismond edge polish on all four sides & hole for wire manager. The glass should cover the length of the table & width of side unit as shown in the drawing. 12	provided with single drawer, ply key board drawer, ply C.P.U. Intelly with ply tootrest, with emanager. 8. other required hardware. The glass shall have plain diamond edge polish on all four sides & hole for wire emanager. The glass should be drawing. 12. Doctors. The glass should cover the length of the table & width of side with the drawing. 13. Patients Examination they board drawer. 14. Quards Table (2° 2° 2° 2° 1° 2° 2° 1° 2° 2° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1°		frame inside advantable with 1.0 thick Laminate on exposed plywood	1			1
py footrest, were manager, & other required hardware. The glass shall new plain diamond edge poils on all flour sides & hole for were manager. The glass should cover the length of the table & width of side. """ Some as items No. 8 without key board drawer." 1 Patients Examinatin Table (6-9° x-2° x-6°) Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Same as items No. 8 without key board drawer. 1 Conference Table 102-0° x 2-0° x 2-6° 1. 1 Providing & flowing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes polish from inside. The the length of the table & with of side units a blook hiron inside. The the length of the table & with of side units a blook hiron inside. The the length of the table & with of side units a blook hiron inside. The table input of the table & with of side units a blook hiron inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer. Ply CPU. Fulley with ply footrest, wire manager, 8 other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 1 Side Units / Crederax 1 Providing & flowing blook for the side of the sid	py footrest, wire manager. & other required hardware. The glass shall have plain diamond edge polish on all four sides & hole for wire manager. The glass should cover the length of the table & width of side unit as shown in the drawing. 12 Doctors Table (4-0" x 2-0" x 2-0" x 2-0") 13 Pailerise Examination Table (6-5" x 2-0" x 2-4") 14 Quarts Table (3-0" x 2-0" x 2-0" x 2-0") 15 Same as items No.8 without key board drawer 16 Same as items No.8 without key board drawer 17 Same as items No.8 without key board drawer 18 Same as items No.8 without key board drawer 19 Providing & fixing table made up of 18 thick Comm. Plywood frame. Intelligence of the short of side unit as shown in the drawing. 10 Conference Table (102-0" x 2-0" x 2-0" x 2-0") 11 Conference Table (102-0" x 2-0" x 2-0" x 2-0") 12 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter Y Work Top (4" x 2-0" x 2-0") 18 Vork Table Running Counter Y Work Top (4" x 2-0" x 2-0") 19 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 19 Work Table Running Counter Y Work Top (4" x 2-0" x 2-0") 10 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table shall be provided with single drawer, by key board drawer, by C.P.U. I trolley with ply footrest, wire manager, & other required hardware, Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 19 Side Units of mm thick comm. plywood framework & fixing the provided with common hardware, and the provided with common hardware and the provided with common hardware and the provided with c		provided with single edge of holes, polish from inside. The table shall be				
nave plan diamond edge polish on all four sides & hole for wire manager. The glass should over the length of the table & width of side unit as shown in the drawing. 12 Doctors Table (4.0" x 2" (2") x 2 = 0") 13 Same as litems No.6 without key board drawer 14 Same as litems No.6 without key board drawer 15 Same as litems No.8 without key board drawer 16 Guards Table (2.0" x 2" over x 4"-6") 17 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 16 Conference Table (10" x 2" x 2" o" x 2" -0") 17 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter / Work Top (4"-6" x 2"-0" x 2"-0") 18 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 19 Work Table Running Counter / Work Top (4"-6" x 2"-0" x 2"-0") 19 Voolrest, with male and up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, because the should be finished with 1.0 thick Laminate on exposed plywood frame, because the polish should be finished with 1.0 thick Laminate on from the constitution of the polish should be finished with 1.0 thick Laminate on provide should have lies shall be providing & fixing side unit made up of 18 mm. thick plywood framework. 18 Coreen to york for chaliman, board room & conference room table. 20 Side Units Credenza. 21 Providing & fixing side unit made up of 18 mm. thick plywood bottom. Drawers should be finished w	nave plan diamond edge polish on all four sides & hole for wire manager. The glass should cover the length of the table & width of side unit as shown in the drawing. 12 Doctors Table (3-0° x 2-0° x 2-0° x 3-6°) 13 Same as items No. 8 without key board drawer 14 Same as items No. 8 without key board drawer 14 Quards Table (3-0° x 2-0° x 2-0° x 3-6°) 15 Board Room Meating Table (1.9° x 3-0° x 3-6° x 2-8°) 16 Board Room Meating Table (1.9° x 3-0° x 3-6° x 2-8°) 17 Providing 8 fixing table made up of 18 link Comm. Plywood frame. The table should be finished with 1.0 thic Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table 8 width of side unit as shown in the drawing. 16 Conference Table (1.9° x 2-0° x 2-0° x 2-0° x 2-0°) 17 Providing 8 fixing table made up of 18 link Comm. Plywood frame. In table should be finished with 1.0 thic Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table 8 width of side unit as shown in the drawing. 17 Work Table Running Counter / Work Top (4-6° x 2-0° x 2-5°) 18 Providing 8 fixing table made up of 18 link Comm. Plywood frame. The table should be finished with 1.0 thic Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be table 8 with of side unit as shown in the drawing. 19 Work Table Running Counter / Work Top (4-6° x 2-0° x 2-5°) 19 Providing 8 fixing table made up of 18 link Comm. Plywood frame. The table should be finished with 1.0 thic Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided to the stable with 1.0 thic Laminate on the shall be provided to the		provided with single drawer, ply key board drawer, ply C.P.U. trolley with				
manager. Ine glass should cover the length of the table & width of side unit as shown in the drawbut key board drawer 10 Patients Examinatin Table (6-6" x 2-0" x 4-6") 11 No 12 Same as Blems No & Windut key board drawer 13 Patients Examinatin Table (6-6" x 2-0" x 4-6") 14 Same as Blems No & Windut key board drawer 15 Same as Blems No & Windut key board drawer 16 Same as Blems No & Windut key board drawer 17 Same as Items No & Windut key board drawer 18 Same as Items No & Windut key board drawer 19 Same as Items No & Windut key board drawer 19 Same as Items No & Windut key board drawer 19 Same as Items No & Windut key board drawer 10 Same as Items No & Windut key board drawer 10 Same as Items No & Windut key board drawer 10 Same as Items No & Windut key board drawer 11 No Same as Items No & Windut key board drawer 12 Same as Items No & Windut he Wi	manager. Ine glass should cover the length of the table & width of side unit as shown in the drawing. 12 Doctors Table (4-0" x 2"-0" x 2"-0" x 2"-0" y 2"-4"-0") 13 Same as thems No. 8 without key board drawer 14 Same as thems No. 8 without key board drawer 15 Same as thems No. 8 without key board drawer 16 Same as thems No. 8 without key board drawer 17 Same as thems No. 8 without key board drawer 18 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 10 Same as thems No. 8 without key board drawer 10 Same as thems No. 8 without key board drawer 11 Same as thems No. 8 without key board drawer 12 No. 8 Same as thems No. 8 without key board drawer 13 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter / Work Table Running Cou		ply footrest, wire manager, & other required hardware. The glass shall	ı			
manager. Ine glass should cover the length of the table & width of side unit as shown in the drawbut key board drawer 10 Patients Examinatin Table (6-6" x 2-0" x 4-6") 11 No 12 Same as Blems No & Windut key board drawer 13 Patients Examinatin Table (6-6" x 2-0" x 4-6") 14 Same as Blems No & Windut key board drawer 15 Same as Blems No & Windut key board drawer 16 Same as Blems No & Windut key board drawer 17 Same as Items No & Windut key board drawer 18 Same as Items No & Windut key board drawer 19 Same as Items No & Windut key board drawer 19 Same as Items No & Windut key board drawer 19 Same as Items No & Windut key board drawer 10 Same as Items No & Windut key board drawer 10 Same as Items No & Windut key board drawer 10 Same as Items No & Windut key board drawer 11 No Same as Items No & Windut key board drawer 12 Same as Items No & Windut he Wi	manager. Ine glass should cover the length of the table & width of side unit as shown in the drawing. 12 Doctors Table (4-0" x 2"-0" x 2"-0" x 2"-0" y 2"-4"-0") 13 Same as thems No. 8 without key board drawer 14 Same as thems No. 8 without key board drawer 15 Same as thems No. 8 without key board drawer 16 Same as thems No. 8 without key board drawer 17 Same as thems No. 8 without key board drawer 18 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 19 Same as thems No. 8 without key board drawer 10 Same as thems No. 8 without key board drawer 10 Same as thems No. 8 without key board drawer 11 Same as thems No. 8 without key board drawer 12 No. 8 Same as thems No. 8 without key board drawer 13 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter / Work Table Running Cou		nave plain diamond edge polish on all four sides & hole for wire				
Content Table (A-0" x 2"-0" x 2"-0") 1 No Same as terms No.5 without key board drawer 1 No Same as terms No.5 without key board drawer 1 No Same as terms No.5 without key board drawer 2 Nos. Same as terms No.5 without key board drawer 2 Nos. Same as terms No.5 without key board drawer 2 Nos. Same as terms No.5 without key board drawer 2 Nos. Same as terms No.5 without key board drawer 2 Nos. Same as terms No.5 without key board drawer 15 Rq.Ft. Nos. Rq.Ft. Nos. 15 Rq.Ft. Nos. Rq.Ft. Nos. 15 Rq.F	10 10 10 10 10 10 10 10		manager. The glass should cover the length of the table & width of side		1		
Same as items No.9 without key board drawer 19 Patients Examinatin Table (6-9" x 2"-0" x 4-6") 19 Patients Examinatin Table (6-9" x 2"-0" x 4-6") 10 Guards Table (2-9" x 2"-0" x 2"-6") 11 No. 12 Same as items No.8 without key board drawer 13 Board Room Meating Table (15-0" x 3"-6" x 2"-6") 14 Clauds Table (2-9" x 2"-0" x 2"-6") 15 Rq.Ft. 15 Rq.Ft. 16 Providing & King table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the slobe 8 width of side unit as shown in the drawing. 16 Conference Table (102"-0" x 2"-0" x 2"-6") 17 Providing & King table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, side edge of holes, polish from inside. The length of the slobe 8 width of side unit as shown in the drawing. 17 Work Table Romining Counter Y Work Tog 1("-6" x 2"-0" x 2"-6") 18 Ward Table Romining Counter Y Work Tog 1("-6" x 2"-0" x 2"-6") 19 Side Units of the made up of 18 thick Comm. Plywood frame. The table shall be provided with single drawer, an play for the side shall be provided with single drawer, an play for the side shall be provided with single drawer, and play frame that the shall be provided with single drawer, and play frame that the shall be provided with single drawer, and play frame that the shall be provided with single drawer, and play frame that the shall be provided with single drawer, and play frame that the shall be provided with single drawer, and play frame that the shall be provided with single drawer, and play frame that the shall be provided with single drawers, and play frame that the shall be provided with single drawers, and play frame that the shall be provided with single drawers and the shall be provided with single string and the shall be provided with single string shall be made of 12 thick. Plywood should have lipping patti and the provided with single string shall be m	Same as items No.8 without key board drawer 12 Patients Examinatin Table (6-8" x 2"-6") 13 Patients Examinatin Table (6-8" x 2"-6") 14 Quards Table (2-9" x 2"-6") 15 Same as items No.8 without key board drawer 16 Soard Room Meating Table (15"-0" x 3"-6" x 2"-6") 17 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & with of side unit as shown in the drawing. 18 Conference Table (102"-0" x 2"-0" x 2"-6" x 2"-6") 19 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the lable & with 1.0 thick Laminate on exposed plywood frame, since edge of holes, polish from inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of vise unit as shown in the drawing. 17 Worth Table Romining Counter Work Top (1-6") x 2"-0"	<u> </u>	Junit as shown in the drawing.				
Same as terms No. 3 without key board drawer 1 Patients Examinatin Table (6-6" x 2" x 4"-6") 1 Patients Examinatin Table (6-6" x 2" x 4"-6") 2 Nos. 3 me as items No. 8 without key board drawer 16 Board Room Meating Table (15-6" x 2" x 5"-6") 17 Providing 8 Buring table made up of 18 thick Comm. Plywood frame. The response of the state of the second of the se	Same as terms No.5 without key board drawer 1 No Same as terms No.5 without key board drawer 2 Nos. Same as terms No.5 without key board drawer 2 Nos. Same as terms No.5 without key board drawer 2 Nos. Same as terms No.5 without key board drawer 15 Rq.Ft. Providing 8 floring table made up of 18 thick Comm. Plywood frame. The drawing should be finished with 1.0 thick Laminate on exposed plywood frame should be finished with 1.0 thick Laminate on exposed plywood frame should be finished with 1.0 thick Laminate on exposed plywood frame inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 102 Fq.Ft. 102 Fq.Ft. 103 Fq.Ft. 103 Fq.Ft. 104 Fq.Ft. 104 Fq.Ft. 104 Fq.Ft. 104 Fq.Ft. 105 F	12	Doctors Table (4'-0" x 2'-0" x 2'-6")	1	No		
13 Patients Examinatin Table (6:6" x 2:0" x 2:0") Same as items No.8 without key board drawer 14 Guards Table (2-9" x 2:0" x 2:0") Same as items No.8 without key board drawer 15 Board Room Meating Table (15:0" x 3:0" x 2:0") Providing 8 frong table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, incide edge of holes, polish from inside. The the length of the table 8 width of side unit as shown in the drawing. 16 Conference Table (12:0" x 2:0" x	13 Patients Examinatin Table (6*-6* x 2*-0* x 4*-6**) Same as items No.8 without key board drawer 14 Guards Table (2*-9* x 2*-0* x 2*-0**) Same as items No.8 without key board drawer 15 Board Room Meating Table (15*-0* x 3*-6* x 2*-0**) Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted missel. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Gredenza 19 Side Units / Gredenza 19 Frooding & fixing table made up of 18 thick Plywood should be fixed be proved as backing. Side unit should have 2 no. of dozen from the painted missel. 19 Side Units / Gredenza 19 Side Units / Gredenza 19 Side Units / Gredenza 20 Nos. 21 Providing & fixing stole meurated on heavy duly drawer siders. Side unit should be meurated on heavy duly drawer siders. Side unit should be side with the side of the s		Same as items No.8 without key board drawer		"		
Same as Items No.8 without key board drawer 2 Nos.	Same as items No.8 without key board drawer 14. Guards Table (2-9" x 2" x 2" e") 15. Board Room Meating Table (15-0" x 2" x 2" e") Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 16. Conference Table (102" 0" x 2" 0" x 2" e") Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17. Whork Table Running Counter / Work Table Running Counter / R	13	Patients Examinatin Table (6'-6" x 2'-0" x 4'-6")	1	No	_	1.
14. Guards Table (2-9" x 2"-0" x 2-6") Same as items No.8 without key board drawer 15. Board Room Meating Table (15-0" x 3"-6" x 2"-6") Providing & finish table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 16. Conference Table (120" x 2"-0" x 2"-6") Providing & finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17. Work Table Running Counter? Work Top (14"-6" x 2"-0" x 2"-6") Providing & King table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C. P.U. trolley with ply footnest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood frame. The table shall be provided with single drawer, ply key board drawer, ply C. P.U. trolley with ply footnest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and entamel painted inside. 18. Coreon Top for Tables Coreon top work for chairman, board room & conference room table 29. Side Units / Gredenza Providing & foning side unit made up of 18 thick Plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & Shutters below. Drawers should be made up of 18 thick Plywood sides & 6 thick Plywood have a power should be made up of 18 thick Plywood sides & 6 thick Plywood should be finished with 10 mm. thick. Laminate of approved shade a coloued external surface & 0.1 paint to non laminated surface. All exposed dependence of 18 thick & 12 thick Plywood should have ploping patil with containing patil patil painting patil plymode scale of	14 Guards Table (2-9" x 2-0" x 2-6") Same as items NO 8 without key board drawer 15 Board Room Meating Table (15-0" x 3-6" x 2-6") Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 16 Conference Table (102" x 2-0" x 2-6") Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter / Work Top (4-5" x 2-0" x 2-6") Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit made up of 18 mm, thick plywood framework. & mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawer should be made up of 18 thick Plywood back as required as proved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patiti All lipping patiti should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminate design. Good quality blockboard shutters should be fixed on SS heavy		Same as items No.8 without key board drawer		110		
Same as items No.8 without key board drawer 16 Board Room Meating Table (15-0" x 3-0" x 2-6" x) = x 2-6" 15 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 102 Rq.Ft.	Same as items No.8 without key board drawer 15 Board Room Meating Table (15-0° x 3-0° x 2-8° x). 16 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 16 Conference Table (102-0° x 2-0° x 2-6°) 17 Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter / Providing & fixing table made up of 18 thick Comm. Plywood frame. Inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P. Ut rolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon top work for chairman, board room & conference room table. 20 Storego Laminer / Lam	14	Guards Table (2'-9" x 2'-0" x 2'-6")	2	Noo		
16 Board Room Meating Table (15-0" x 3"-6" x 2"-6") Providing & Rining table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of aide unit as shown in the drawing. Providing & Rining table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. Work Table Running Counter / Work Top (4"-6" x"-0" x"-2"-2"-0") Providing & Rining table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with aminate on front and enamel painted inside. 18	16 Board Room Meating Table (15°0" x 3°0" x 2°0" x		Same as items No.8 without key board drawer	-	NOS.		
Providing & Brining table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 16 Conference Table (102-0" x 2-0" x 2-6") Providing & Rining table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter Work Top (4-6" x 2-0" x 2-6") Providing & Bring table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and ehrante planted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 20 Store to work for chairman, board room & conference room table 21 Side Units / Credenza Providing & fixing side unit made up of 18 thick Plywood framework & Orm. 22 Nos. 23 Nos. 24 Nos. 25 Nos. 26 Providing & fixing side unit made up of 18 thick Plywood sides & 6 thick Plywood bottom. Drawers should be made up of 18 thick Plywood should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood should have lipping patti All Ripping pattis should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood bould have lipping patti All Ripping pattis should be finished with plantifrench polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks with common key for set of drawers etc	Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 16. Conference Table (102°0° x 2°0° x 2°6°) Providing & finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17. Work Table Running Counter / Work Table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footnest, wire manager, & other required hardware / Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and ehamel painted inside. 18. Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19. Side Units / Credenza Providing & fining side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood sides & 6 thick Plywood bottom. Drawers should be made up of 18 thick Plywood sides & 6 thick Plywood bottom. Drawers should be meaved to no na laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patt All Pluping patts should be finished with 1.0 mm. thick Laminate or front and enamel painted inside 20. Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework. 12 mm. thick plywood and finished with laminate on front and enamel painted inside 20. Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework. 12 mm. thick comm. ply for both verticals and horizontal members. The	15	Board Room Meating Table (15'-0" x 3'-6" x 2'-6")	15	D. Et		
table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 16 Conference Table (102-0" x 2-0" x 2-0") Providing & Ring table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter (Work Top (4-6" x 2-0" x 2-6"). Providing & Ring table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chalman, beard room & conference room table 19 Side Units / Cradenza Providing & Ring isdie unit made up of 18 mm. thick plywood framework. & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood bottom. Drawers should be mounted on heavy duty drawers sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti All lipping patti should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Codrej make locks with common handles, Godrej make locks with from handles with 1.0 mm. thick	lable should be finished with 1.0 thick Laminate on exposed plywood farme, niside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 16. Conference Table (1920-"w.2-0" x.2-6") Providing & fixing table made up of 18 thick Comm. Plywood farme. The table should be finished with 1.0 thick Laminate on exposed plywood farme, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17. Work Table Running Counter / Work Top (4-5" x.2-0" x.2-6") Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood farme, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C-Pu. trolley with ply footrest, wife manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18. Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19. Side Units / Credenza Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood shade & fish the Plywood fascia, 6 thick Plywood shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood shade with common key for set of drawers etc. complete as per design. Coord in alke locks with common key for set of drawers etc. complete as per design. Good quality blockboard shutters should be finished with plant/french polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 29. Stora		Providing & fixing table made up of 18 thick Comm. Plywood frame. The	15	Rq.Ft.		-
Ifame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 102 Rq.Ft.	Fame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 102 Rq.Ft.		table should be finished with 1.0 thick Laminate on expected plants at				
Itable & width of side unit as shown in the drawing. 102 Rq.Ft.	Table & width of side unit as shown in the drawing. 10 10 10 10 10 10 10 1		frame inside edge of holes polich from inside. The the least to				
Conference Table (102-0" x 2-0" x 2	Conference Table (102-0" x2-0" x2-0") 102 Rq.Ft.		table & width of side unit as shown in the drawing		1	1	
Providing & Rixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter (Work Top (4.5° x 2°0° x 2.5°) Providing & Rixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, plx. Pt. Ut trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon top work for chairman, board room & conference room table 19 Side Units / Tordenza. 22 Nos. Providing & Rixing side unit'made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/ferench polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. 20 Storage Cabinet Providing & Rixing storage units made up 18 mm. thick plywood framework; 12 mm. thick plywood should have plipping patti on it. Lipping patti should be finished with paint on it. Lipping patti should be finished with french polish on it. The cost should include necessary handles, magnetic actives, 62 or plywood should have plipping patti on it. Lipping patti should be finished with french polish on it. The cost should include necessary handles, magnetic actives, 62 or plymood s	Providing & Rixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter / Work Top (4'-6''x 2'-0''x 2'-6") 40 Rg.Ft. Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza 19 Side Units / Credenza 20 Nos. Providing & fixing side unit made up of 18 mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood slots & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping pattis should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ad surfaces. All exposed edges of plywood should have jipping pattis on it. The cost should include necessary handles, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing & Rixing s	16	Conference Table (102'0" v 2'0" v 2'0")				
table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter / Work Top (4.6° x 2.0° x 2.6° x). Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table should be finished with single drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top twork for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should he made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be meade up of 18 thick Plywood fascia, 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood should be finished with 1.0 mm. thick laminate from external sulf & oil paint to non laminate de surfaces. All exposed edges of plywood should have lipping patt in it. Lipping patt is hould be finished with 1.0 mm. thick laminate from external sloke & oil paint to non laminate de surfaces. All exposed edges of p	fable should be finished with 1.0 thick Laminate on exposed plywood fame, noiside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter / Work Top (4-6** 2-0** 2-6**) Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chaliman, board room & conference room table 19 Side Units / Oredenza 19 Providing & fixing side unit made up of 18 mm. thick plywood framework & 6 mm. thick plywood as backing. Side unit should have 2 n. or drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer silders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common hardles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood should have plipping patti on it. Upping patti should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate de surfaces. All exposed edges of Plywood should have lipping patti on it. Upping patti should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate de surfaces. All exposed edges of plywood should have plipping p	- 10	Providing & fixing table mode up of 40 think 0	102	Rq.Ft.		
Irame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing.	Irame, inside edge of holes, polish from inside. The the length of the table & width of side unit as shown in the drawing. 17 Work Table Running Counter / Work Top (4-6" x 2'-0" x 2'-0") 40 Rq.Ft.		table should be finished with 4.0 this table should be finished with 4.0 this table.				
Table & width of side unit is as shown in the drawing. 17 Work Table Running Counter / Work Top (4-6* x 2-0*x 2-6*)	Table & width of side unit as shown in the drawing. Two the Table Running Counter / Work Top (4-6* x²-0* x²-6**) 40 Rq.Ft.		frame incide edge of believe with 1.0 thick Laminate on exposed plywood				1
Table & width of side unit is as shown in the drawing. 17 Work Table Running Counter / Work Top (4-6* x 2-0*x 2-6*)	Table & width of side unit as shown in the drawing. Two the Table Running Counter / Work Top (4-6* x²-0* x²-6**) 40 Rq.Ft.		table 8 width of city and the length of the			1	1
Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick corm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit made up of 18mm, thick plywood framework & 6mm, thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood slottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping pattit All lipping pattir's should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping pattit All lipping pattir's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with 1.0 mm. thick plywood framework, 1.2 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on the false celling level or 7-0" ht. The facing edges. Of all ply wood sections should be	Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. Coreon Top for Tables Coreon top twork for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood side & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping pattit All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with 1.0 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 11 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 16" depth. They shall be made of 19 mm thick comm. ply for both ve		table & width of side unit as shown in the drawing.			1	1
Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick corm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit made up of 18mm, thick plywood framework & 6mm, thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood slottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping pattit All lipping pattir's should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping pattit All lipping pattir's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with 1.0 mm. thick plywood framework, 1.2 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on the false celling level or 7-0" ht. The facing edges. Of all ply wood sections should be	Providing & fixing table made up of 18 thick Comm. Plywood frame. The table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. Coreon Top for Tables Coreon top twork for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood side & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping pattit All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with 1.0 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 11 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 16" depth. They shall be made of 19 mm thick comm. ply for both ve	17	Work Table Running Counter / Work Top (4'-6"x 2'-0"x 2'-6")	40	Ra.Ft.		
table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18	table should be finished with 1.0 thick Laminate on exposed plywood frame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18		Providing & fixing table made up of 18 thick Comm. Plywood frame. The		1		
rame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply key Dc.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18	rame, inside edge of holes, polish from inside. The table shall be provided with single drawer, ply key board drawer, ply c.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer silders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping pattis should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common hay for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with 1.0 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with 1.0 mm. thick laminate from external members. The bottom of the units shall be at 3' from FFL. The		table should be finished with 1.0 thick Laminate on exposed plywood		1	1	
provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18	provided with single drawer, ply key board drawer, ply C.P.U. trolley with ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18		frame, inside edge of holes, polish from inside. The table shall be			1	1
ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. Coreon Top for Tables Providing & fixing side unit' made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood stost. 2 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with manager of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges. of all ply wood sections should be provided with lip	ply footrest, wire manager, & other required hardware. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 29 Nos. Providing & fixing side unit'made up of 18mm. thick plywood framework & 6mm. thick plywood a backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patit All lipping patit's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common hardles, Godrej make locks with patient of the patient of		provided with single drawer, ply key board drawer, ply C.P.U. trolley with				
made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood bottom. Drawers should be mounted on heavy duty drawer siders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with laminate on front and enamel painted inside 20 Storage Cabinet 21 Storage Cabinet 22 Storage units should be finished with laminate on front and enamel painted inside 23 Storage units should be finished with 1.0 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. 24 Good quality blockboard shutters should be fixed on SS heavy hinges 25 Storage units should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 26 Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7"-0" ht. The facing edges of all ply wood	made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet 21 Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. 22 God quality blockboard shutters should be fixed on SS heavy hinges Storage units, should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 116" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom		ply footrest, wire manager, & other required hardware. Drawers to be		1	1	
and enamel painted inside. 18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit'made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & sututers below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminated suprace shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patt's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patt in it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 116" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FL. The top of storages shall touch the false ceiling level or 7"-0" ht. The facing edges. Of all ply wood sections should be provided with lipping patti fipished with French polish with approved laminate on	and enamel painted inside. 8 Coreon Top for Tables Coreon Top work for chairman, board room & conference room table 2 Side Units / Credenza 2 Nos. Providing & fixing side unit' made up of 18mm. thick plywood framework & 6mm. thick plywood a backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer silders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common hardles, Godrej make locks with common hey for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 116" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7".0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish on it. The cos		made of 12 mm thick comm. plywood and finished with laminate on front				
18 Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & Rixing side unit'made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer siders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping pattit All lipping pattis should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Pigeon Hol	Coreon Top for Tables Coreon top work for chairman, board room & conference room table 19 Side Units / Gredenza Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Pi		and enamel painted inside				
Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit' made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer silders. Side unit should be finished with 10 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti all lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common handles, Godrej make locks with common hey for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 10 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 16" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished with 1.0mm thick Laminate (suede finish) of approved make	Coreon top work for chairman, board room & conference room table 19 Side Units / Credenza Providing & fixing side unit' made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common haples, Godrej make locks with common haples, Godrej make locks with common haples, Godrej make locks with common hypwood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 10 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted	18	Coreon Top for Tables	240	054		_
Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common handles, Godrej make locks with common hywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units, should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toliet Block Size 3"0"X2"-0" 5 Nos.	Providing & fixing side unit' made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood slades. & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer siders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej water de sign. Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood shoul have ploping patti on the provided with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have jipping patti on the provided with 1.0 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall both the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lip			340	Sq.Ft.		1
Providing & fixing side unit'made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood sacia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patt in it. Lipping patt is should be finished with 1 no m. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patt in it. Lipping patt is should be read to the finished with French polish on it. The cost should be rinished with French polish on it. The cost should be rinished with French polish on it. The cost should be rinished members. The bottom of the unit shall be at 3" from FFL. The top of storages shall bouch the false ceiling level or 7-0" ht. The facing edges, of all ply wood sections should be provided with lipping patti finished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site bondition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architec	Providing & fixing side unit made up of 18mm. thick plywood framework & 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common heavy of the cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 10 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patt on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site	19	Side Units / Credenza		 		
drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet 2270 Sq.Ft. Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall buch the false ceiling level or 7'-0" ht. The facing edges. Of all ply wood sections should be provided with lipping patti finished with french polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the	& 6mm. thick plywood as backing. Side unit should have 2 no. of drawers above & shutters below. Drawers should be made up of 18 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet 2270 Sq.Ft. Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall bouch the false ceiling level or 7'-0" ht. The facing edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Archit			22	Nos.		
drawers above & shutters below. Drawers should be made up of 18 thick Plywood backai, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cablinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7"-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede f	drawers above & shutters below. Drawers should be made up of 18 thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges. of all ply wood sections should be provided with lipping patti finished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0 mm thick Laminate (suede finish) of approved make. 21 Mirror In		& 6mm, thick plywood as backing Side unit about the second				
thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7"-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make.	thick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti. All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet 22 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6' depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3' from FFL. The top of storages shall touch the false ceiling level or 7'-0' ht. The facing edges of all ply wood sections should be provided with lipping patti fipished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of		drawers above 8 shutters below Drawers about have 2 no. of		1		
bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with Trench polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0 mm thick Laminate (suede finish) of approved make.	bottom. Drawers should be mounted on heavy duty drawer sliders. Side unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with Tench polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges. of all ply wood sections should be provided with lipping patti finished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make.		thick Divised feeting 40 thick Division should be made up of 18		1		1
unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common handles, Godrej make locks with common plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet 2270 Sq.Ft. Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges. of all ply wood sections should be provided with lipping patti finished with 1-0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	unit should be finished with 1.0 mm. thick. Laminate of approved shade & colour on external surface & oil paint to non laminated surface. All exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common handles, Godrej make locks with common plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 16" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site pondition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		trick Plywood fascia, 12 thick Plywood sides & 6 thick Plywood		1		
exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet 2270 Sq.Ft. Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished with Prench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cablinet 2270 Sq.Ft. Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		bottom. Drawers should be mounted on heavy duty drawer sliders. Side				
exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7"-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	exposed edges of 18 thick & 12 thick Plywood should have lipping patti All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		unit should be finished with 1.0 mm. thick. Laminate of approved shade		=1		
All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished with French polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	All lipping patti's should be finished with paint/french polish on it. The cost should include necessary hardware, handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixing storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have lipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Tollet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		& colour on external surface & oil paint to non laminated surface. All				
cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		exposed edges of 18 thick & 12 thick Plywood should have lipping patti				
cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	cost should include necessary hardware, handles, Godrej make locks with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		All lipping patti's should be finished with paint/french polish on it. The				
with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7"-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Tollet Block Size 3'-0"X2'-0" P& F mirror Modi float in tollet block with 6mm bevilled on edges and	with common handles, Godrej make locks with common key for set of drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7"-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Tollet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		cost should include necessary hardware, handles. Godrei make locks				
drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	drawers etc. complete as per design. Drawers to be made of 12 mm thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		with common handles, Godrej make locks with common key for set of				
thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.	thick comm. plywood and finished with laminate on front and enamel painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		drawers etc. complete as per design. Drawers to be made of 12 mm				3.50
painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges. of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	painted inside 20 Storage Cabinet Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges. of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.		thick comm. plywood and finished with laminate on front and enamel		2.83		
Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		painted inside	(37)			
Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	Providing & fixing storage units made up 18 mm. thick plywood framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	20		2270	C~ E⁴		
framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	framework, 12 mm. thick plywood back as required as per design. Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.			2210	Sy.Ft.		
Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	Good quality blockboard shutters should be fixed on SS heavy hinges Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and		framework, 12 mm, thick plywood back as required as per desired				
Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.	Storage units. should be finished with 1.0 mm. thick laminate from external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.		Good quality blockboard shutters should be fived as DO bears.				
external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti fipished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	external side & oil paint to non laminate ed surfaces. All exposed edges of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.		Storage units should be finished with 10 mm third laminates				
of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.	of plywood should have Jipping patti on it. Lipping patti should be finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and		external side & oil paint to pop laminate and authors Att				
finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping pattifinished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	finished with French polish on it. The cost should include necessary handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping pattifinished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.		of pluwood should have liming notification.				
handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.	handles, magnetic catches, Godrej make locks etc. complete as per design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		finished with French police and it. Lipping patti should be				
design. 21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.	21 Pigeon Hole Shelves For Dispatch Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping pattifinished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		handles respect to set the cost should include necessary				
Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" Sq. F.t. 60 Sq.F.t. 60 Sq.F.t. 60 Sq.F.t. 60 Sq.F.t. 60 No.	Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and		nanules, magnetic catches, Godrej make locks etc. complete as per				
Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and						
Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	Providing and fixing Pegeon Hole units of full height and 1'6" depth. They shall be made of 19 mm thick comm. ply for both verticals and horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	21	Pigeon Hole Shelves For Dispatch	60	Sq.F.t.		
horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.		Providing and fixing Pegeon Hole units of full height and 1'6" depth.				
horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	horizontal members. The bottom of the unit shall be at 3" from FFL. The top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos.		rney snall be made of 19 mm thick comm. ply for both verticals and		- 1		
top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	top of storages shall touch the false ceiling level or 7'-0" ht. The facing edges of all ply wood sections should be provided with lipping patti finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	- 1	horizontal members. The bottom of the unit shall be at 3" from FFL. The	1			
edges of all ply wood sections should be provided with lipping pattifinished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	edges of all ply wood sections should be provided with lipping pattifinished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	.	top of storages shall touch the false ceiling level or 7'-0" ht. The facing				365
finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	finished withFrench polish with approved laminate on all the shutter edges. The size of pegeon hole to be adjusted equally as per the site condition, approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	यहि	edges of all ply wood sections should be provided with lipping pattil				
edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	edges. The size of pegeon hole to be adjusted equally as per the site condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	John !	finished withFrench polish with approved laminate on all the shutter				
condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	condition. approximate size of each pegeon hole should be 10" x 10" and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	2	edges. The size of pegeon hole to be adjusted equally as per the site				
and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	and in consultation with Architect. All the Internal surfaces shall be finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	*	condition, approximate size of each pegeon hole should be 10" v 10"				
finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	finished with 1.0mm thick Laminate (suede finish) of approved make. 21 Mirror In Toilet Block Size 3'-0"X2'-0" P& F mirror Modi float in toilet block with 6mm bevilled on edges and	8.4	and in consultation with Architect All the Internal surfaces shall be	=			
21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	21 Mirror In Toilet Block Size 3'-0"X2'-0" 5 Nos. P& F mirror Modi float in toilet block with 6mm bevilled on edges and	गामतः	finished with 1 0mm thick I aminate (sucdo finish) of carround and a		1	- [
P& F mirror Modi float in toilet block with 6mm bevilled on edges and	P& F mirror Modi float in toilet block with 6mm bevilled on edges and	- 1	minoriou with 1.5mm thick Laminate (suede linish) of approved make.		- 1		
P& F mirror Modi float in toilet block with 6mm bevilled on edges and	P& F mirror Modi float in toilet block with 6mm bevilled on edges and	21	Mirror In Toilet Block Size 21 00 VOL 00				
fixed on SS Stude. Size of mirror 3 Feet v. 0 Feet	fixed on SS Studs. Size of mirror 3 Feet x 2 Feet		P& F mirror Modi float in toilet block with Community	5	Nos.		
	plined on 35 Studs. Size of mirror 3 Feet x 2 Feet	[2	ived on SS Stude Size of mirror 2 Fact 1.25				

22	Downley Control Alexandria CVIII				
	Powder Coated Aluminium Sliding Window:	100	Sq.Ft.	_	
	Providing and fixing aluminium sliding powder coated. The Frame				
1	should be 2" x 1 1/2" wide sections with tracks on all the sides & drain				
1	tray system for the bottom frame. The shutters should be of suitable 2" x				
- 1	4" and the bottom marile. The shutters should be of suitable 2 x				
- 1	1" sections for top & bottom member & 1 5/8" x 1" for vertical with 6 mm.				
1	thick approved make clear float glass and beading shall be used. The			l	
- 1	tracks will be fixed on 2" x 1" aluminium BOX frame (Heavy Duty 2"			l	
- 1	thick frames (14 gauge) - approved make)				
- 1	Note: rate shall be inclusive of passages fittings lasted by the				
1	Note: rate shall be inclusive of necessary fittings, locks, handles, best				
	quality rollers, necessary hardware items, etc.				
23	Roller Blinds	3125	Sq.Ft.		
	Providing & fixing in place 100 mm. Roller blinds of approved make,				
1	quality and colour shade & pattern. Rate shall include necessary scotch				
1	guard treatment on both sides. The overlaps should be uniform &				
	adequate.				
24	Utility Counter (2'-0" Top Wide Counter With 1'-6" Depth Storage	10	Rg.Ft.		
	Below ; Height - Upto 4'-6")				
	Providing and laying Utility Counter using 19mm thick Comm. Ply top,				
1	sides and back, with Storage units below the counter (450 - 600 mm			1	
1	depth). 19mm thick Comm. Ply shutter with box type hinges of approved	l l			
1	make 2 steem base liming failed with box type filliges of approved			1	
	make & steam beach lipping finished with melamine. All external				
1	surfaces to be finished in 1.0 mm laminate (suede finish) of approved				1
	make.				j 1
	Division of shutters shall be made equally according to the Height /			- 6	
	Length of the storage. A 19 mm thick comm. Ply shelf on battens shall	I			
1	be provided in middle. 19 mm thick Comm. Ply shelves removable type			30	
	supported on side steem basels was the first transfer of the side of the steem basels was the steem of the steem basels was the steem of the steem o				
	supported on side steam beach wood battens (polished) on both sides	,			
	at 16" interval (approximately / divided equally) shall be provided.				
	Suitable steam beach moulding (as advised by Bank/ Architect) 19mm x				
	7mm size, with melamine shall be provided to the edge of the counter				, ,
	top. All inner surfaces including shutters shall be finished with approved				
1	laminate.				
	Rate shall be inclusive of all necessary approved fittings like hinges,				
	locks, 100 mm long brushed finish handles, tower bolts and any				
	necessary hardware items.		_		
25	Shutters Below Granite Counters	27	Sq.Ft.		
	Providing and fixing 19mm thick BWR ply shutters with ply frame,				
	skirting gap as shown in the drawing shall be maintained. Division of				
1	shutters shall be made equally assenting to the length of the				
	shutters shall be made equally according to the length of the counter.	- 1			
	Shutters shall be hinged to the framework and finished with 1.0mm thick	Į.			
1	Laminate (suede finish) of approved shade from outside, applied with				
1					
1	lapproved oil paint from the inside and edges of shutters with steam				
	approved oil paint from the inside and edges of shutters with steam				9
	beach lipping. Rate shall be inclusive of all necessary approved fittings				я
					3
	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items.				
26	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables				
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" Ht.)	10	Nos.		
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht)	10 4	Nos.		
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht)				
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as				
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with				
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary				
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame				
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect.				
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to				
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom				
a.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to				
a. b.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom	4	Nos.		
a. b.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards				
a. b.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of	4	Nos.		
a. b.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board	4	Nos.		
a. b.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved	4	Nos.		
a. b.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x	4	Nos.		
a. b.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine	4	Nos.		
a. b.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish.	4	Nos.		
a. b.	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine	4	Nos.		
27	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be	4	Nos.		
27	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the	4	Nos.		
27	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition measurement (rate) and not consider separately.	50	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition measurement (rate) and not consider separately. Key Box	4	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition measurement (rate) and not consider separately. Key Box Providing and fixing key box of size 1'-6"x1'-6"x 6" with all sides and	50	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition measurement (rate) and not consider separately. Key Box Providing and fixing key box of size 1'-6"x1'-6"x 6" with all sides and back with 19 mm thick comm. Ply wood and lockable glass shutters in	50	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition measurement (rate) and not consider separately. Key Box Providing and fixing key box of size 1'-6"x1'-6"x 6" with all sides and	50	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition measurement (rate) and not consider separately. Key Box Providing and fixing key box of size 1'-6"x1'-6"x 6" with all sides and back with 19 mm thick comm. Ply wood and lockable glass shutters in 19 mm ply , with 5 mm glass. Necessary hooks to be provided inside the	50	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition measurement (rate) and not consider separately. Key Box Providing and fixing key box of size 1'-6"x1'-6"x 6" with all sides and back with 19 mm thick comm. Ply wood and lockable glass shutters in 19 mm ply , with 5 mm glass. Necessary hooks to be provided inside the box. All exposed areas and inside to be finished with 1 mm thick	50	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht.) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition/measurement (rate) and not consider separately. Key-Box Providing and fixing key box of size 1'-6"x1'-6"x 6" with all sides and back with 19 mm thick comm. Ply wood and lockable glass shutters in 19 mm ply , with 5 mm glass. Necessary hooks to be provided inside the box. All exposed areas and inside to be finished with 1 mm thick laminate of approved shade. The edges of shutter and box to be lipped	50	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition/measurement (rate) and not consider separately. Key-Box Providing and fixing key box of size 1'-6"x1'-6"x 6" with all sides and back with 19 mm thick comm. Ply wood and lockable glass shutters in 19 mm ply , with 5 mm glass. Necessary hooks to be provided inside the box. All exposed areas and inside to be finished with 1 mm thick laminate of approved shade. The edges of shutter and box to be lipped with steam beach beeding polished with melamine. Rate shall be	50	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition measurement (rate) and not consider separately. Key Box Providing and fixing key box of size 1'-6"x1'-6"x 6" with all sides and back with 19 mm thick comm. Ply wood and lockable glass shutters in 19 mm ply, with 5 mm glass. Necessary hooks to be provided inside the box. All exposed areas and inside to be finished with 1 mm thick laminate of approved shade. The edges of shutter and box to be lipped with steam beach beeding polished with melamine. Rate shall be inclusive of all necessary approved fittings like hinges, locks, hooks etc.	50	Nos.		
27 28	beach lipping. Rate shall be inclusive of all necessary approved fittings like hinges, ball catch, handle, and any necessary hardware items. Side / Corner Tables Corner Tables (1'-6" X 1'-6" X 1'-6" Ht.) Center Tables (1'-6" X 2'-6" X 1'-6" Ht) Providing and making corner / side tables of above mentioned size as per drawing. Table top shall consist of 12 mm. thick float glass with champhered edge (beveled edge) fitted to the frames with necessary arrangement. The base shall be made up of Steam beach wood frame as directed by the Bank / Architect. It should be with 4 Nos of 35mmx35mm for vertical members tied to each other with horizontal members of 20mm x 35mm frames at bottom and All wooden frames to be finished with melamine. Pin-Up Boards Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox. Rs.250 / Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish. Note: Only soft bords provided on other than the partitions will be measured and soft board made in the partitions will be the part of the partition/measurement (rate) and not consider separately. Key-Box Providing and fixing key box of size 1'-6"x1'-6"x 6" with all sides and back with 19 mm thick comm. Ply wood and lockable glass shutters in 19 mm ply , with 5 mm glass. Necessary hooks to be provided inside the box. All exposed areas and inside to be finished with 1 mm thick laminate of approved shade. The edges of shutter and box to be lipped with steam beach beeding polished with melamine. Rate shall be	50	Nos.		

_	29 Boxing For Rolling Shutter					
	29 Boxing For Rolling Shutter Providing & fixing 3/4" BWR ply boxing for the rolling shutters. Necessar	350	Sq.Ft			
		y		1		
	perposed sides by Ittill lattifiate and internally with enamel naint	"				
	Note: rate shall include all necessary hardware fittings, etc.					
		35	Sq.Ft			
	Providing and fixing trap doors consisting of 1/2" thick comm. pl	у				
	shutters with a clear opening of 4.5" opening for smooth operation of shutters and rest is closed with mirror screws (for opening for servicing)	of				
	The shallers shall be imished with approved 1mm laminate from	-				
	1- 1/2 Wood Sections shall be brouded for proper summer	.1				
	Total trace stidil be inclusive of necessary fittings like himner	f			- 1	
3		Ί				
	Tam Official Door Mals (4 -l) A /-II''	11	Nos.	+	_	
	Providing & laying in place Synthetic Door Mats (3M) of sizes not less that 4' x 2').					
32	2 Frost Film / Etching Film Over Glass	0000				
	Providing and fixing etching film as directed by Ropk (Architect 6	2000	Sq.Ft.			
	joxocos area (for additional area other than 1feet donth and full is not a	.1				
	Iglaco, along with portion spec.) to proper level with out air hubbles /					
33	Todo / Todo etc. Complete			1		
	Sofa Sets - (Fabric Cost B.R. Rs. 300 / Mts. Teal Green Colour Sample To Be Got Approved)				\dashv	
	a Single Seater		1			
	b. Double Seater	3	Nos.			
_	c. Three Seater	13	Nos.			
	Providing and fixing sofa set to detail as shown in drawing about 60cm	10	1108.	+		
	I wide and about botth high comprising second class CAL MOOD			1		
	Individually 30 x 40 with 8mm thick com plywood covering on all		l .		- 1	
	sides. Seats finished with spring hooked to MS plate 25mm width fixed to the seat frame. Both seat frame and back covered with layer of jute					
	Join and Joinin latex rupper (2 layer for seat alone) finished with 40					
	product mining and uphostered to shape with fabric (basic price Do 200/m)					
	The real of the back also and the linder surface of the cost finish all				- 1	
	with Gada cloth 8mm ply below seat Note: (For sofas motorials tills)					
	ploans, latex rubbel, gadacioth, spring tabric etc. to be approved by the					
_	Attended to Balik).					
4	Oil Bound Distemper Paint	1000	Sq.Ft.		_	
	Providing and application of cement/acrylic based putty of 3 Coats,				_	
	Sanding of the surface free of undulations, application of 1 coat of primer and 2 coats of Oil Bound Distance of 1				- 1	
	primer and 2 coats of Oil Bound Distemper paint of approved make and shade as per layout policy.					
5	Acrylic Emulsion Paint	4500				
	Providing and application of cement/acrylic based putty of 3 Coats	4500	Sq.Ft.			
	position of 1 cost of					
	primer and 2 coats of Acrylic Emulsion paint of approved make and					
5	shade as per layout policy.					
_	Synthetic Enamel	950	Sq.Ft.			
	Painting on new / old surfaces with two or more coats, to give an even shade, of synthetic enamel (as / shade approved by the Architect) of					
	approved brank. It shall include for preparing the surfaces clean, even	- 1				
	land smooth with thoroughly brushing with broom scratching with next					
	land said papering respectively. It shall also include for filling of holes I	- 1				
	Infloring and stopping before priming coat of approved primer	- 1				
	The rate shall include cost of all materials shifting of furniture and other					
	sundries etc., all complete to the satisfaction of the Architect.		- 1			
	Total Tandarad Cont (5)					
	Total Tendered Cost (Furnishing) (Rs.)					
	Less - Discount (Rs.)					
٦	Balance (Rs.)					
\dashv	Add - Goods & Services Tax (CGST) (Rs.)					
\dashv	Add - Goods & Services Tax (SGST) (Rs.)					
+	Add - Transportation / Cartage (Rs.)					
_	Net Amount (Rs.)					
	Amount in words					
	Amount in words -				1	
- 1	Dunasa	- 1	- 1		1	
- 1	Rupees	- 1	1			
- 1	Rupees					
- 1	Rupees		1			
- 1	Rupees					